



CHAMÄLEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAMÄLEON GMBH
RUDOLF-DIESEL-STRASSE 8A
69115 HEIDELBERG
GERMANY

FON 0049 (0) 6221 - 520 440
FAX 0049 (0) 6221 - 520 449
MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

TECHNICAL DATA SHEET

CHAMÄLEON SPOT BLENDER

Article number:	13405, 13408
Intended use:	Car refinishing Product/ Preparation
General characteristics:	Special solvent mixture to be used for dissolving spray dust at spot repairs and add-on paintings.
Recommended for:	Chamäleon 103, 133, 105, 155, 106, or similar 2K acrylic clear or 2K AC coats

Usage:

After applying one of the above paints, spray immediately CHAMÄLEON SPOT BLENDER on the stained surfaces. After 10 - 15 seconds dissolve the spray dust with CHAMÄLEON SPOT BLENDER.

Remarks:

Do not use on thermoplastic acryls.

Storage: At least 4 years if stored tightly closed in original containers.

All products should be disposed of in relation to the regulations of the environmental health authorities. Protect your Environment!

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical Data Sheet, please contact the supplier via:
info@chamaeleon-produktion.de

For safety information, please refer to the corresponding Safety Data Sheet.