



CHAMALEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAMALEON GMBH
RUDOLF-DIESEL-STRASSE 8A
69115 HEIDELBERG
GERMANY

FON 0049 (0) 6221 - 520 440
FAX 0049 (0) 6221 - 520 449
MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

TECHNICAL DATA SHEET

Revision date: 16.01.2026

AEROSOL CHAIN LUBRICANT

Article number:

27013

Colour:

transparent yellow

Intended use:

Car refinishing product/Lubricant

General characteristics:

Chain Lubricant provides long-lasting lubrication for all chain-driven vehicles and systems due to its unique composition. It has very strong adhesion, making it particularly suitable for fast-running and heavily loaded chains, such as those on (cross) motorcycles. In addition, it is formulated as dilatant (reverse thixotropic), which prevents the oil from running off the chain even at high speed. This product is equipped with a special cap containing a tube and spray nozzle for precise application in hard-to-reach areas.

- very low coefficient of friction
- o-ring safe
- excellent mechanical and thermal stability
- weather-resistant
- resistant to weak acids and alkalis

Fields of application:

Chain drives of all kinds such as bicycles, motorcycles, scooters, agricultural machinery, in shipping, car repair workshops or maintenance facilities.

TECHNICAL CHARACTERISTICS

Base: mineral oil

Smell: characteristic

Temperature resistant: -50°C to +200°C



CHAMALEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAMALEON GMBH
RUDOLF-DIESEL-STRASSE 8A
69115 HEIDELBERG
GERMANY

FON 0049 (0) 6221 - 520 440
FAX 0049 (0) 6221 - 520 449
MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

APPLICATION PROCESS

Before use, carefully read and observe the warning texts on the label!

Processing conditions:

Please only use in an adequate ventilated environment with an ample supply of fresh air. Processing temperature should be from +12 °C to +25 °C and max. air humidity should not exceed 80%.

Processing tips:

- The substrate must be clean, dry, free from rust and grease. Remove old lubricants, if possible
- The aerosol should have room temperature
- Before use, shake the aerosol for 2 min
- Spray the Chain Lubricant evenly onto the chain
- During the initial flow phase, when the product can penetrate well into the treated chain, it appears foamy
- The optimal lubrication is obtained after evaporation of the solvent (after approx. 5 min)

VOC regulation:

EU limit value: Category B/e 840 g/l

This product contains max. 486.7 g/l

Shelf life:

120 months, if stored in tightly closed original containers

This release replaces all eventually earlier issued versions.

For additional information, not contained in this technical data sheet, please contact the supplier under:

e-mail: info@chamaeleon-produktion.de

For safety information, please refer to the corresponding Safety data sheet.