



CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449 MAIL INFO@CHAMAELEON-PRODUKTION.DE WEB WWW.CHAMAELEON-PRODUKTION.DE

SAFETY DATA SHEET according to 1907/2006/EC, Article 31

Revision date: 14.06.2022

<u>1- IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/</u> <u>UNDERTAKING</u>

Product details Trade name: Spray putty Article number: 14175 Relevant identified uses of the substance or mixture and uses advised against: No further relevant information available. Intended use: Car refinishing product/Knife filler/ Surfacer Manufacturer/Supplier: Chamäleon GmbH Rudolf-Diesel-Straße, 8a, 69115 Heidelberg Germany Further information obtainable from: Product Safety Department Information in case of emergency: + 49 70024112112 (CH)

<u>2 – HAZARDS IDENTIFICATION</u>

Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

Repr. 2 H361d Suspected of damaging the unborn child. STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.



STEUERNUMMER/TAX NR.: DE 231468544 EORI NR./CUSTOMS NR.: DE 6029442 / HRB 9778 GESCHÄFTSFÜHRER/CEO: SASCHA HAGEMANN





CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

 FON
 0049 (0) 6221 - 520 440

 FAX
 0049 (0) 6221 - 520 449

 MAIL
 INFO@CHAMAELEON-PRODUKTION.DE

 WBW
 WWW.CHAMAELEON-PRODUKTION.DE

Skin Irrit. 2 H315 Causes skin irritation.Eye Irrit. 2 H319 Causes serious eye irritation.Skin Sens. 1 H317 May cause an allergic skin reaction.STOT SE 3 H335 May cause respiratory irritation.

Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02 GHS07 GHS08

Signal word Danger

Hazard-determining components of labelling:

Styrene

maleic anhydride

cobalt bis(2-ethylhexanoate)

Fatty acids, C14-18 and C16-18-unsatd., maleated

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H361d Suspected of damaging the unborn child.

H335 May cause respiratory irritation.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Additional information:

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist. **Other hazards**

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.



CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

 FON
 0049 (0) 6221 - 520 440

 FAX
 0049 (0) 6221 - 520 449

 MAIL
 INFO@CHAMAELEON-PRODUKTION.DE

 WEB
 WWW.CHAMAELEON-PRODUKTION.DE

3- COMPOSITION/INFORMATION ON INGREDIENTS

Chemical characterisation: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:				
CAS: 100-42-5 EINECS: 202-851-5 Reg.nr.: 01-2119457861-32	Styrene Flam. Liq. 3, H226; Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	≥10-<25%		
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46	Ethyl acetate Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	2.5-<10%		
CAS: 85711-46-2 EINECS: 288-306-2 Reg.nr.: 01-2119976378-19	Fatty acids, C14-18 and C16-18-unsatd., maleated Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1B, H317	≥0.1-<1%		
CAS: 67-56-1 EINECS: 200-659-6	methanol Flam. Liq. 2, H225; Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331; STOT SE 1, H370	<1%		
CAS: 108-31-6 EINECS: 203-571-6 Reg.nr.: 01-2119472428-31	maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317	≥0.001-<0.1%		

Additional information: For the wording of the listed hazard phrases refer to section 16

<u> 4– FIRST - AID MEASURE</u>

Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:

Generally the product does not irritate the skin.

Immediately rinse with water.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. **After swallowing:** If symptoms persist consult doctor.

STEUERNUMMER/TAX NR.: DE 231468544 EORI NR./CUSTOMS NR.: DE 6029442 / HRB 9778 GESCHÄFTSFÜHRER/CEO: SASCHA HAGEMANN







CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

FON 0049 (0) 6221 - 520 440 0049 (0) 6221 - 520 449 MAIL INFO@CHAMAELEON-PRODUKTION.DE WEB WWW.CHAMAELEON-PRODUKTION.DE

Indication of any immediate medical attention and special treatment needed No further relevant information available.

<u>5– FIRE - FIGHTING MEASURE</u>

Extinguishing media Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam. For safety reasons unsuitable extinguishing agents: Water with full jet Special hazards arising from the substance or mixture: During heating or in case of fire poisonous gases are produced. Advice for firefighters Protective equipment: Mouth respiratory protective device.

6- ACCIDENTAL RELEASE MEASURE

Personal precautions, protective equipment and emergency procedures:

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Environmental precautions: Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

<u>7– HANDLING AND STORAGE</u>

Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.

Information about fire - and explosion protection:







CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449 MAIL INFO@CHAMAELEON-PRODUKTION.DE WBW.CHAMAELEON-PRODUKTION.DE

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
Conditions for safe storage, including any incompatibilities
Storage:
Requirements to be met by storerooms and receptacles: No special requirements.
Information about storage in one common storage facility: Store away from foodstuffs.
Further information about storage conditions: Keep container tightly sealed.
Storage class: 3

Specific end use(s): No further relevant information available.

8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Additional information about design of technical facilities: No further data; see item 7.

Ingredients with limit values that require monitoring at the workplace:

100-42-5 Styrene		
WEL	Short-term value: 1080 mg/m ³ , 250 ppm	
	Long-term value: 430 mg/m ³ , 100 ppm	
141-78-6 Ethyl acetate		
WEL	Short-term value: 1468 mg/m ³ , 400 ppm	
	Long-term value: 734 mg/m ³ , 200 ppm	
67-56-1 methanol		
WEL	Short-term value: 333 mg/m ³ , 250 ppm	
	Long-term value: 266 mg/m ³ , 200 ppm	
	Sk	
108-31-6 maleic anhydride		
WEL	Short-term value: 3 mg/m ³	
	Long-term value: 1 mg/m ³	
	Sen	

Additional information: The lists valid during the making were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

BANK HEIDELBERGER VOLKSBANK EG IBAN DE78 6729 0000 0042 8627 03 BIC GENODE61HD1

5







CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449 MAIL INFO@CHAMAELEON-PRODUKTION.DE WWW.CHAMAELEON-PRODUKTION.DE

Avoid contact with the eyes and skin.

Respiratory protection:

Filter A/P2 (EN 141, EN 143)

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation

Material of gloves

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material: Value for the permeation: Level ≤ 2 **Eye protection:** Tightly sealed goggles

Information on basic physical and	chemical properties
General Information	
Appearance:	
Form:	Viscous
Colour:	Beige
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	145.2 °C
Flash point:	23 °C (DIN 53213)
Flammability (solid, gas):	Not applicable.
Ignition temperature:	480 °C (DIN 51794)
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.

<u>9 – PHYSICAL AND CHEMICAL PROPERTIES</u>

STEUERNUMMER/TAX NR.: DE 231468544 EORI NR./CUSTOMS NR.: DE 6029442 / HRB 9778 GESCHÄFTSFÜHRER/CEO: SASCHA HAGEMANN

Chamäleon GmbH- Safety Data Sheet



CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

 FON
 0049 (0) 6221 - 520 440

 FAX
 0049 (0) 6221 - 520 449

 MAIL
 INFO@CHAMAELEON-PRODUKTION.DE

 WBB
 WWW.CHAMAELEON-PRODUKTION.DE

-

Explosive properties:	<i>Product is not explosive. However, formation of explosive air/vapour mixtures are possible.</i>
Explosion limits:	
Lower:	1.2 Vol %
Upper:	8.9 Vol %
Vapor pressure at 20 °C:	6 hPa
Density at 20°C:	1.5 g/cm ³ (DIN 53217)
Relative density	Not determined.
Vapour density	Not determined.
Evaporation rate	Not determined.
Solubility in /	
Miscibility with water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic at 20 °C:	>60 s (ISO 6 mm)
Solvent content:	
VOC (EC)	5.31 %
Solids content (weight-%):	71.6 %
Other information:	No further relevant information available.

<u>10– STABILITY AND REACTIVITY</u>

Reactivity No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions: No dangerous reactions known.

Conditions to avoid: No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: Carbon monoxide.

<u>11– TOXILOGICAL INFORMATION</u>

Information on toxicological effects Acute toxicity: Based on available data, the classification criteria are not met. Primary irritant effect:

STEUERNUMMER/TAX NR.: DE 231468544 EORI NR./CUSTOMS NR.: DE 6029442 / HRB 9778 GESCHÄFTSFÜHRER/CEO: SASCHA HAGEMANN

Chamäleon GmbH- Safety Data Sheet



CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449 MAIL INFO@CHAMAELEON-PRODUKTION.DE WWW.CHAMAELEON-PRODUKTION.DE

Skin corrosion/irritation: Causes skin irritation. Serious eye damage/irritation: Causes serious eye irritation. Respiratory or skin sensitization: May cause an allergic skin reaction. Additional toxicological information: CMR effects (carcinogenity, mutagenicity and toxicity for reproduction) Germ cell mutagenicity: Based on available data, the classification criteria are not met. Carcinogenicity: Based on available data, the classification criteria are not met. **Reproductive toxicity:** Suspected of damaging the unborn child. **STOT-single exposure:** May cause respiratory irritation. **STOT-repeated exposure** Causes damage to the hearing organs through prolonged or repeated exposure. Aspiration hazard: Based on available data, the classification criteria are not met.

<u>12 – ECOLOGICAL INFORMATION</u>

Toxicity Aquatic toxicity: No further relevant information available. Persistence and degradability: No further relevant information available. Bioaccumulative potential: No further relevant information available. Mobility in soil: No further relevant information available. Additional ecological information: General notes: Water hazard class 2 (German Regulation) : hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground. Results of PBT and vPvB assessment PBT: Not applicable. vPvB: Not applicable. Other adverse effects: No further relevant information available.

13– DISPOSAL CONSIDERATION

Waste treatment methods Recommendation

STEUERNUMMER/TAX NR.: DE 231468544 EORI NR./CUSTOMS NR.: DE 6029442 / HRB 9778 GESCHÄFTSFÜHRER/CEO: SASCHA HAGEMANN







CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449 MAIL INFO@CHAMAELEON-PRODUKTION.DE WEB WWW.CHAMAELEON-PRODUKTION.DE

Must not be disposed together with household garbage. Do not allow product to reach sewage system. **Uncleaned packaging:** Recommendation: Disposal must be made according to official regulations

<u>14– TRANSPORT INFORMATION</u>

UN-Number ADR, IMDG, IATA

UN3269

UN proper shipping name ADR IMDG, IATA

UN3269 POLYESTER RESIN KIT POLYESTER RESIN KIT

Transport hazard class(es) ADR



Class Label 3 (F3) Flammable liquids. 3

IMDG, IATA



Class Label

3 Flammable liquids. 3

Packing group ADR, IMDG, IATA

Environmental hazards: Marine pollutant:

EMS Number:

III

No

Special precautions for user

Warning: Flammable liquids. Hazard identification number (Kemler code): -F-E,S-D **Stowage Category** А

STEUERNUMMER/TAX NR.: DE 231468544 EORI NR./CUSTOMS NR.: DE 6029442 / HRB 9778 GESCHÄFTSFÜHRER/CEO: SASCHA HAGEMANN



CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

 FON
 0049 (0) 6221 - 520 440

 FAX
 0049 (0) 6221 - 520 449

 MAIL
 INFO@CHAMAELEON-PRODUKTION.DE

 WBW
 WWW.CHAMAELEON-PRODUKTION.DE

Transport in bulk according to Annex II of			
Marpol and the IBC Code:	Not applicable.		
Transport/Additional information	on:		
ADR			
Limited quantities (LQ)	5L		
Transport category	3		
Tunnel restriction code	E		
IMDG			
Limited quantities (LQ)	5L		
UN "Model Regulation":	UN 3269 POLYESTER RESIN KIT, 3, III		

<u> 15 – REGULATORY INFORMATION</u>

Safety, health and environmental regulations/legislation specific for the substance or mixture Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t **Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t **National regulations:**

Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
I	<1
NK	25-50

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

<u>16-OTHER INFORMATION</u>

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.





CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

 FON
 0049 (0) 6221 - 520 440

 FAX
 0049 (0) 6221 - 520 449

 MAIL
 INFO@CHAMAELEON-PRODUKTION.DE

 WBW
 WWW.CHAMAELEON-PRODUKTION.DE

- H311 Toxic in contact with skin.
 - H314 Causes severe skin burns and eye damage.
 - H315 Causes skin irritation.
 - H317 May cause an allergic skin reaction.
 - H318 Causes serious eye damage.
 - H319 Causes serious eye irritation.
 - H331 Toxic if inhaled.
 - H332 Harmful if inhaled.
 - H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 - H335 May cause respiratory irritation.
 - H336 May cause drowsiness or dizziness.
 - H361d Suspected of damaging the unborn child.
 - H370 Causes damage to organs.
 - H372 Causes damage to organs through prolonged or repeated exposure.
 - H412 Harmful to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008:

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids - Category 2

Flam. Liq. 3: Flammable liquids - Category 3

Acute Tox. 3: Acute toxicity - Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation - Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

BANKHEIDELBERGER VOLKSBANK EGIBANDE78 6729 0000 0042 8627 03BICGENODE61HD1

11



CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449 MAIL INFO®CHAMAELEON-PRODUKTION.DE WEB WWW.CHAMAELEON-PRODUKTION.DE

Skin Sens. 1A: Skin sensitisation – Category 1A
Skin Sens. 1B: Skin sensitisation – Category 1B
Repr. 2: Reproductive toxicity – Category 2
STOT SE 1: Specific target organ toxicity (single exposure) – Category 1
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
Asp. Tox. 1: Aspiration hazard – Category 1
Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

The information contained in these sheets is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.