



CHAMÄLEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAMÄLEON GMBH  
RUDOLF-DIESEL-STRASSE 8A  
69115 HEIDELBERG  
GERMANY

FON 0049 (0) 6221 - 520 440  
FAX 0049 (0) 6221 - 520 449  
MAIL [INFO@CHAMAELEON-PRODUKTION.DE](mailto:INFO@CHAMAELEON-PRODUKTION.DE)  
WEB [WWW.CHAMAELEON-PRODUKTION.DE](http://WWW.CHAMAELEON-PRODUKTION.DE)

## ***TECHNICAL DATA SHEET***

### **CHAMÄLEON MASKING TAPE**

<b>Article number:</b>	<b>48212; 48222, 48242, 48252</b>
<b>Intended use:</b>	Masking the car body when refinishing
<b>Technical characteristics:</b>	
<b>Heat resistant::</b>	90°C / 60min
<b>Wides:</b>	18mm*50m, 24mm*50m, 36mm*50m, 48mm*50m
<b><u>Film properties:</u></b>	
<b>Type of Film:</b>	Impregnated Crepe Paper
<b>Film Thickness:</b>	125 µm
<b>MD tensile strength:</b>	38 N/cm
<b>Elongation at Break MD:</b>	Min 7 %
<b><u>Adhesive properties:</u></b>	
<b>Type of Adhesive:</b>	Solvent-borne, rubber resin
<b>Colour:</b>	Brown
<b>Adhesion to steel plate:</b>	2.3 N/cm
<b>Prior to use:</b>	Carefully check that the contact surfaces are totally dry and clean from oil, grease and dust.
<b>Storage conditions:</b>	around 21 °C and 50% relative humidity.

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical Data Sheet, please contact the supplier via:  
[info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)

For safety information, please refer to the corresponding Safety Data Sheet.