



CHAMALEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAMALEON GMBH
RUDOLF-DIESEL-STRASSE 8A
69115 HEIDELBERG
GERMANY

FON 0049 (0) 6221 - 520 440
FAX 0049 (0) 6221 - 520 449
MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

TECHNICAL DATA SHEET

Revision date: 16.01.2026

AEROSOL ELECTRICAL CONTACT CLEANER

Article number:

27012

Colour:

transparent

Intended use:

Car refinishing product/Lubricant

General characteristics:

High-quality cleaning agent that ensures long-lasting conductivity in electrical connections. This product is equipped with a special cap containing a tube and spray nozzle for precise application in hard-to-reach areas. Thanks to the use of a special 360° valve, it can be sprayed in any position

- high cleaning power without leaving residues
- moisture repellent
- corrosion inhibiting
- non-corrosive
- non-conductive

Fields of application:

Connectors, motors, wiring and connections on cars and motorcycles, bicycles, printed circuit boards, switches, pressure plates, contacts, plugs, television sets, radios, tools, and audio systems.

TECHNICAL CHARACTERISTICS

Base: aliphatic hydrocarbons with alcohol

Smell: characteristic

APPLICATION PROCESS

Before use, carefully read and observe the warning texts on the label!



CHAMALEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAMALEON GMBH
RUDOLF-DIESEL-STRASSE 8A
69115 HEIDELBERG
GERMANY

FON 0049 (0) 6221 - 520 440
FAX 0049 (0) 6221 - 520 449
MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

Processing conditions:

Please only use in an adequate ventilated environment with an ample supply of fresh air. Processing temperature should be from +10 °C to +25 °C and max. air humidity should not exceed 60%.

Processing tips:

- The aerosol should have room temperature
- Before use, shake the aerosol for 2 min and spray a sample
- Switch off all electrical and electronic equipment before handling to ensure that no voltage is present
- Spray the Electrical Contact Cleaner evenly onto the parts
- After treatment, wait until all flammable solvent vapours have completely dissipated (at least 15 min) before switching devices back on

ATTENTION: Do not spray on carburettors or radiators

VOC regulation:

EU limit value: Category B/e 840 g/l

This product contains max. 722.0 g/l

Shelf life:

120 months, if stored in tightly closed original containers

This release replaces all eventually earlier issued versions.

For additional information, not contained in this technical data sheet, please contact the supplier under:

e-mail: info@chamaeleon-produktion.de

For safety information, please refer to the corresponding Safety data sheet.