

TECHNICAL DATA SHEET

Revision date: 01.07.2024

BITUMEN BRUSHABLE

Article number:	37111
Colour:	black
Intended use:	Car refinishing product/ Protective coating
General characteristics:	<p>Bitumen brushable is a durable corrosion protection based on wax/bitumen for floor pans, entry sections and wheelhouses, etc.</p> <ul style="list-style-type: none"> ▪ excellent adhesion and elasticity ▪ shock- and scratch-resistance ▪ long-term non-sticking flexible film ▪ good sound deadening properties ▪ non-drip application ▪ good resistance to de-icing salt

PAINTING PREPARATION PROCESS

Hardener: without hardener
Dilution: without thinner; ready to use

APPLICATION PROCESS

Before use, carefully read and observe the warning texts on the label!

Processing conditions:

Please only use in an adequate ventilated environment with an ample supply of fresh air. Processing temperature should be at least +12 °C and max. air humidity should not exceed 80%.

Application method	
Brush or special UBS brush	
DFT	Consumption
approx. 3 mm	1 - 2 m ² /l

■ Processing tips

- The substrate must be clean, dry, free from rust and grease. Remove old/loose coatings or primers.

ATTENTION

Do not apply on engine, transmission, sump, cardan shaft, exhaust pipes, axles, springs, shock absorbers, brake cables, grease nipples etc., mask these parts before!

VOC regulation:

EU limit value: Category B/e 840 g/l

This product contains max. 840 g/l VOC

Shelf life:

36 months, if stored in tightly closed original containers

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical Data Sheet, please contact the supplier via:
info@chamaeleon-produktion.de

For safety information, please refer to the corresponding Safety Data Sheet.