

TECHNICAL DATA SHEET

Revision date: 10.04.2025

MULTI-PURPOSE SPRAY

Article number:	27009												
Colour:	transparent												
Intended use:	Car refinishing product/Lubricant												
General characteristics:	<p>Combines lubricating, protecting, and cleaning properties into one powerful product. Effectively removes oil, grease, wax, and tar, what makes Multi-purpose spray indispensable for a wide range of applications.</p> <ul style="list-style-type: none">▪ special nozzle simplifies application on hard-to-reach places▪ excellent penetration and moisture-repellent properties▪ creates a protective barrier against corrosion <p>Fields of application:</p> <table><tr><td>▪ chains</td><td>▪ locks</td><td>▪ garden tools</td></tr><tr><td>▪ fastenings</td><td>▪ tools</td><td>▪ machinery</td></tr><tr><td>▪ fasteners</td><td>▪ home trainers</td><td>▪ bicycle</td></tr><tr><td>▪ pedals</td><td>▪ skelers</td><td>▪ skateboards</td></tr></table>	▪ chains	▪ locks	▪ garden tools	▪ fastenings	▪ tools	▪ machinery	▪ fasteners	▪ home trainers	▪ bicycle	▪ pedals	▪ skelers	▪ skateboards
▪ chains	▪ locks	▪ garden tools											
▪ fastenings	▪ tools	▪ machinery											
▪ fasteners	▪ home trainers	▪ bicycle											
▪ pedals	▪ skelers	▪ skateboards											

TECHNICAL CHARACTERISTICS

Base: mineral oil with additives

Smell: characteristic

APPLICATION PROCESS

Before use, carefully read and observe the warning texts on the label!

Processing conditions:

Please only use in an adequate ventilated environment with an ample supply of fresh air. Processing temperature should be from +12 °C to +25 °C and max. air humidity should not exceed 80%.

Processing tips:

- The aerosol should have room temperature
- Before use, test the compatibility of the surface
- Before use, shake the aerosol for 2 min and spray a sample
- Apply in the desired quantity
- The optimal lubrication is obtained after evaporation of the solvent

VOC regulation:

EU limit value: Category B/e 840 g/l

This product contains max 603.7 g/l VOC

Shelf life:

120 months, if stored in tightly closed original containers.

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical Data Sheet, please contact the supplier under:

e-mail: info@chamaeleon-produktion.de

For safety information, please refer to the corresponding Safety Data Sheet.