

**TECHNICAL DATA SHEET**

Revision date: 01.10.2023

**UNDERBODY PROTECTION BITUMEN**

**Article number:** 37102  
**Colour:** Black  
**Intended use:** Car refinishing product/ Protective coating

**General characteristics:** Underbody protection Bitumen is a highly resistant coating for floor pans, wheel houses etc. It provides a durable protection against corrosion, de-icing salt and stone-chip. Excellent adhesion, shock- and scratch-resistant, long-term flexible film, good sound deadening properties, non-drip application

**PAINTING PREPARATION PROCESS**

**Dilution:** ready to spray  
**Pot life at 20 °C:** -

**APPLICATION PROCESS**

Before use, carefully read and observe the warning texts on the label!

**Processing conditions:**

Please only use in an adequate ventilated environment with an ample supply of fresh air. Processing temperature should be at least +12 °C and max. air humidity should not exceed 80%.

Application method	Pressure	Nozzle
Brush or special UBS brush	-	-

Spraying operations	DFT	Consumption
-	approx. 3 mm	1 - 2 m2/l

**Processing tips:**

The floor pan must be cleaned thoroughly. It must be dry, free from dust, grease, oil and rust.

Old non-adherent underbody coating must be removed.

Do not apply on engine, transmission, sump, cardan shaft, exhaust pipes, axles, springs, shock absorber, brake cables, grease nipples, etc.

### **VOC regulation:**

EU limit value: Category B/e 840 g/l

This product contains max. 840 g/l VOC

### **Shelf life:**

36 months, if stored in tightly closed original containers

This release replaces all eventually earlier issued versions.

For additional information, not contained in this technical data sheet, please contact the supplier under:

e-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)

For safety information, please refer to the corresponding Safety data sheet.