

TECHNICAL DATA SHEET*Revision date: 10.10.2024***ELASTIFIER**

Article number:	13601								
Colour:	transparent								
Intended use:	Car refinishing product/ Paint additive								
General characteristics:	<p>The additive is used to improve elasticity of acrylic 2K paints and 2K clear coats. Electrifier prevents cracking and chipping of the primer/filler and paint coating on elastic and deformable elements. It can also be used to elasticise paint coatings on metal elements exposed to stone chipping (e.g. front strip, bonnet).</p> <p>Substrates:</p> <table><tr><td>▪ PC/PBT</td><td>▪ RPG</td><td>▪ PPE Alloys</td><td>▪ ABS</td></tr><tr><td>▪ PC/ASA</td><td>▪ PPO</td><td>▪ PP</td><td>▪ EPDM</td></tr></table>	▪ PC/PBT	▪ RPG	▪ PPE Alloys	▪ ABS	▪ PC/ASA	▪ PPO	▪ PP	▪ EPDM
▪ PC/PBT	▪ RPG	▪ PPE Alloys	▪ ABS						
▪ PC/ASA	▪ PPO	▪ PP	▪ EPDM						

PAINTING PREPARATION PROCESS**Mixing:** Basic paint + 10 - 50 % Elastifier**APPLICATION PROCESS**

Before use, carefully read and observe the warning texts on the label!

Processing conditions:

Please only use in an adequate ventilated environment with an ample supply of fresh air. Processing temperature should be at least +12 °C and max. air humidity should not exceed 80%.

Processing tips:

- Please note that Elastifier does NOT change the mixing ratio of the 2K paint or 2K clear coat to hardener.
- Depending on the added quantity of Elastifier, the drying time can exceed 100% of normal.

- **Shelf life:**
36 months, if stored in tightly closed original containers

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical Data Sheet, please contact the supplier via:
info@chamaeleon-produktion.de

For safety information, please refer to the corresponding Safety Data Sheet.