

TECHNICAL DATA SHEET**FINE LINE TAPE****Article number:** 48360, 48361**Intended use:** Car refinishing product/ Masking**General characteristics:** Fine Line Tape is a high temperature fine line tape which adheres excellent to a wide variety of surfaces. This tape will perform in the presence of 150°C temperature for at least one hour. It follows contours and remains in place as long as necessary. Leaves no residue upon removal.**Construction:**

Adhesive	Rubber
Carrier	Plasticized PVC film
	Dark blue

Applications:**Car:**

- Multi-colour paint applications
- Aftermarket autobody
- Fine line masking tape
- Plastic parts (bumpers)

Industry:

- Multi-colour paint applications
- Not recommended for outdoor use

Technical characteristics:

Total thickness	0,16 mm
Adhesive strength	6,5 N/25 mm
Tensile strength	77,5 N/25 mm
Elongation	130%
Maximum temperature	+150°C
Solvent resistance	Very good



CHAMALEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAMALEON GMBH
RUDOLF-DIESEL-STRASSE 8A
69115 HEIDELBERG
GERMANY

FON 0049 (0) 6221 - 520 440
FAX 0049 (0) 6221 - 520 449
MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

Recommendations for use:

Temperature: between +15°C and +30°C. Surface must be clean and free from dust and grease. Pressure sensitive adhesive must be applied with a maximum of pressure in order to achieve maximum pressure level. The indicated level of performance will be reached after a bonding period of 24HRS at +23°C.

Storage:

Clean and dry in a well ventilated area, preferably at a temperature between +10°C and +30°C.

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical Data Sheet, please contact the supplier via:
info@chamaeleon-produktion.de

For safety information, please refer to the corresponding Safety Data Sheet.