

TECHNICAL DATA SHEET

Revision date: 10.10.2024

UNI THINNER UNI THINNER SLOW

Article number:	13225, 13228 / 13235, 13238
Colour:	transparent
Intended use:	Car refinishing product/ Thinner, dilutant
General characteristics:	Special mixture of solvents used to dilute 2K acrylic paints, clear coats, primers and base coats. UNI thinner can be used to adjust the spraying viscosity, to improve application and to clean tools. The type of thinner and concentration depends on the ambient temperature and the viscosity of the base product.

Type of UNI Thinner	Conditions	Description
SLOW	> 25°C	Type of thinner used in high temperatures conditions
STANDARD	12°C - 25°C	Type of thinner used in standard temperatures conditions

APPLICATION PROCESS

Before use, carefully read and observe the warning texts on the label!

Processing conditions:

Please only use in an adequate ventilated environment with an ample supply of fresh air. Processing temperature should be at least +12 °C and max. air humidity should not exceed 80%.

Shelf life:

36 months, if stored in tightly closed original containers

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical Data Sheet, please contact the supplier via:
info@chamaeleon-produktion.de

For safety information, please refer to the corresponding Safety Data Sheet.