

TECHNICAL DATA SHEET

Revision date: 27.11.2024

CHROME EFFECT GOLD EFFECT

Article number:	26725, 26726												
Colour:	silver chrome, gold chrome												
Intended use:	Car refinishing product/ Paint												
General characteristics:	<p>Metallic paint based on special resins and pigments designed for decoration of surfaces and objects that require a chrome-like finish.</p> <ul style="list-style-type: none">▪ fast drying▪ excellent adhesion▪ good coverage▪ long-lasting and extra-glossy mirroring effect <p>Fields of application:</p> <table><tr><td>▪ ferrous surfaces</td><td>▪ stone</td><td>▪ wood</td></tr><tr><td>▪ plastics (abs, pvc, etc.)</td><td>▪ brass</td><td>▪ paper</td></tr><tr><td>▪ aluminum</td><td>▪ copper</td><td>▪ terracotta</td></tr><tr><td>▪ bronze</td><td>▪ cardboard</td><td>▪ wicker</td></tr></table>	▪ ferrous surfaces	▪ stone	▪ wood	▪ plastics (abs, pvc, etc.)	▪ brass	▪ paper	▪ aluminum	▪ copper	▪ terracotta	▪ bronze	▪ cardboard	▪ wicker
▪ ferrous surfaces	▪ stone	▪ wood											
▪ plastics (abs, pvc, etc.)	▪ brass	▪ paper											
▪ aluminum	▪ copper	▪ terracotta											
▪ bronze	▪ cardboard	▪ wicker											

TECHNICAL CHARACTERISTICS

Base: hydrocarbon resin

Smell: characteristic

Consumption: 1 - 1.5 m²

Heat resistant: up to 100 - 120 ° C

APPLICATION PROCESS

Before use, carefully read and observe the warning texts on the label!

Processing conditions:

Please only use in an adequate ventilated environment with an ample supply of fresh air. Processing temperature should be from +15 °C to +25 °C and max. air humidity should not exceed 80%.

■ **Processing tips:**

- The substrate must be clean, dry, free from rust and grease. Remove old loose coatings and primers
- Beforehand, mask the parts that shouldn't be painted
- Degrease the surface
- Wear a respirator (type A2/P3 is recommended)
- The aerosol should have room temperature
- Before use, shake the aerosol for 2 min and spray a sample
- The number of suggested coats depends on normal surface absorptions. Surfaces with higher absorptions require more coats. It is recommended to use a suitable primer when possible
- Distance to the surface should be approximately 20 - 30 cm
- To get even coverage of the product, we recommend shaking the can between layers
- To achieve the best effect, apply several light passes in a cross pattern, waiting at least 20 s- 30 sec between the passes
- Remove overspray/spillage with acetone and/or paint thinner. NOTE: Some surfaces can be damaged by thinner or acetone

Drying	Dry to touch	Completely dry
Object temperature 20 °C	15 - 25 min	24 h

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

ATTENTION

- Indoor use only
- The aerosol cap does not completely correspond to the effect obtained by the paint.
- Not recommended for objects subject to rubbing or excessive handling as the leafing effect will disappear.
- The mirror effect is preserved for at least 12 months and gradually fades over time. The original effect can be restored by applying new coats of paint.
- DO NOT OVERCOAT WITH CLEAR COAT.
- The best result of Chrome effect (silver) is obtained on smooth and pre-treated surfaces with a glossy black background.

VOC regulation:

EU limit value: Category B/e 840 g/l

This product contains max. 530 g/l (Gold effect), 581.7 g/l (Chrome effect)

Shelf life:

24 months, if stored in tightly closed original containers.

This release replaces all eventually earlier issued versions.



CHAMÄLEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAMÄLEON GMBH
RUDOLF-DIESEL-STRASSE 8A
69115 HEIDELBERG
GERMANY

FON 0049 (0) 6221 - 520 440
FAX 0049 (0) 6221 - 520 449
MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

- For additional information, not contained in this Technical Data Sheet, please contact the supplier via:
info@chamaeleon-produktion.de
For safety information, please refer to the corresponding Safety Data Sheet.