

**TECHNICAL DATA SHEET***Revision date: 30.10.2024***BASIC AEROSOLS: WHEEL PAINT**

<b>Article number:</b>	<b>26104</b>
<b>Colour:</b>	silver
<b>Intended use:</b>	Car refinishing product/ Paint
<b>General characteristics:</b>	<p>A fast-drying 1K acrylic paint with high coverage, excellent adhesion and good surface hardness.</p> <ul style="list-style-type: none"><li>▪ non-fading and UV resistant</li><li>• resistant to petrol, chemicals and de-icing salt</li><li>▪ wear and scratch resistant</li><li>▪ lasting gloss</li></ul> <p><b>Fields of application:</b></p> <ul style="list-style-type: none"><li>▪ steel</li><li>▪ light metal rims</li><li>▪ hubcaps</li></ul>

**TECHNICAL CHARACTERISTICS****Base:** acrylic resin**Smell:** characteristic**Degree of gloss:** >75 GU**Consumption:** 4 - 5 m<sup>2</sup>**Temperature resistant:** up to 110°C**APPLICATION PROCESS**

Before use, carefully read and observe the warning texts on the label!

**Processing conditions:**

Please only use in an adequate ventilated environment with an ample supply of fresh air. Processing temperature should be from +10 °C to +25 °C and max. air humidity should not exceed 80%.

## Processing tips:

- The substrate must be clean, dry, free from rust and grease. Remove old loose coatings or primers
- Apply a suitable primer to prevent rust or corrosion and get better adhesion (for example Chamäleon Aluminium- or Basic aerosol Primer)
- After drying, sand the base layer with P400-P800
- Degrease the surface again
- The aerosol should have room temperature
- Before use, shake the aerosol for 2 min
- Distance to the surface should be approximately 25 - 30 cm
- Apply the Wheel paint in several thin layers
- Keep a flash off time 3 - 5 min between each spray pass (depending on the layer thickness)
- In order to obtain high gloss, apply a finishing coat of Chamäleon clear coat
- Clean the valve after use (turn aerosol upside down and press the nozzle for approximately 5 sec)

Drying	Dust free	Set to touch	Overcoatable
Object temperature 20 °C	5 - 10 min	10 - 20 min	2 h

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

## VOC regulation:

EU limit value: Category B/e 840 g/l

This product contains max. 688.6 g/l VOC

## Shelf life:

120 months in tightly closed original container

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical Data Sheet, please contact the supplier under:

e-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)

For safety information, please refer to the corresponding Safety Data Sheet.