

## TECHNICAL DATA SHEET

Revision date: 10.04.2025

## AEROSOL PAINT FOR FABRICS &amp; CARPETS

Article number:	26802 (black), 26812 (anthracite)
Colour:	black, anthracite
Intended use:	Car refinishing product/ Paint
General characteristics:	<p>High-performance aerosol designed to restore and enhance the original color of textile mats and carpets with precision and ease of application.</p> <ul style="list-style-type: none"><li>▪ high coverage</li><li>▪ excellent adhesion</li><li>▪ covers stains and wear patches</li><li>▪ applicable on rubber and textile mats</li></ul>

## TECHNICAL CHARACTERISTICS

**Base:** acrylic**Smell:** characteristic**Consumption:** 1.25 - 1.75 m<sup>2</sup> (400 ml)**Temperature resistant:** up to 90°C

## APPLICATION PROCESS

Before use, carefully read and observe the warning texts on the label!

**Processing conditions:**

Please only use in an adequate ventilated environment with an ample supply of fresh air. Processing temperature should be from +12°C to +25 °C and max. air humidity should not exceed 80%.

**Processing tips:**

- The substrate must be clean, dry, free of dust and grease. Remove old loose coatings
- Beforehand, mask the parts that shouldn't be painted
- Wear a respirator (type A2/P3 is recommended)

- The aerosol should have room temperature
- Before use, test the compatibility of the surface
- Before use, shake the aerosol for 2 min and spray a sample
- Apply in several thin layers
- Distance to the surface should be 15 - 20 cm
- Keep a flash off time 5 min between each spray pass
- After each spray pass, we recommend to brush the wet film to ensure that the carpet fibres are thoroughly covered with paint and do not stick together.
- Clean the valve after use (turn aerosol upside down and press the nozzle for approximately 5 sec)

Drying	Dust free	Set to touch	Completely dry
Object temperature 20 °C	5 min	30 min	1 h

The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.

### VOC regulation:

EU limit value: Category B/e 840 g/l

The art. 26802 contains max 704.7 g/l VOC

The art. 26812 contains max 661.2 g/l VOC

### Shelf life:

120 months, if stored in tightly closed original containers.

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical Data Sheet, please contact the supplier under:

e-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)

For safety information, please refer to the corresponding Safety Data Sheet.