

**TECHNICAL DATA SHEET**

Revision date: 05.05.2025

**AEROSOL CONTROL GUIDE COAT**

Article number:	26051
Colour:	black
Intended use:	Car refinishing product/ Preparation
General characteristics:	Fast-drying control coat for detecting surface imperfections after levelling and sanding such as scratches, pits, and pinholes which remain visible as black spots. These flaws can be easily removed by sanding, applying putty, or using a suitable Chamäleon filler primer.

**TECHNICAL CHARACTERISTICS****Base:** nitrocombi resin**Smell:** characteristic**Consumption:** 3.0 - 4.0 m<sup>2</sup> (500 ml)**APPLICATION PROCESS**

Before use, carefully read and observe the warning texts on the label!

**Processing conditions:**

Please only use in an adequate ventilated environment with an ample supply of fresh air. Processing temperature should be from +12 °C to +25 °C and max. air humidity should not exceed 80%.

**Processing tips:**

- Wear a respirator (type A2/P3 is recommended)
- The aerosol should have room temperature
- Before use, shake the aerosol for 2 min
- Distance to the surface should be approx. 25 - 30 cm
- Apply a thin layer of Control guide coat and allow to dry for 10 min

- The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.
- Sand the surface till the Control guide coat is completely removed
- Clean the valve after use (turn aerosol upside down and press the nozzle for approximately 5 sec)

### VOC regulation:

EU limit value: Category B/e 840 g/l

This product contains max. 704.9 g/l VOC

### Shelf life:

120 months, if stored in tightly closed original container

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical Data Sheet, please contact the supplier under:

e-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)

For safety information, please refer to the corresponding Safety Data Sheet.