

TECHNICAL DATA SHEET

Revision date: 10.10.2024

SPOT BLENDER

| | |
|--------------------------|---|
| Article number: | 13405, 13408 |
| Colour: | transparent |
| Intended use: | Car refinishing product/ Thinner, dilutant |
| General characteristics: | <p>Spot blender (fade-out thinner) is a special mixture of solvents used to "blend" the edges of spot repairs into the old clear coat.</p> <p>Usage:</p> <ul style="list-style-type: none">▪ for smoothing the transition between old and new paint coating in the transition area▪ as a fade-out thinner in combination with following products: 2K clear coats or 2K PU/acryl topcoats |

APPLICATION PROCESS

Before use, carefully read and observe the warning texts on the label!

Processing conditions:

Please only use in an adequate ventilated environment with an ample supply of fresh air. Processing temperature should be at least +12°C and max. air humidity should not exceed 80%.

Processing tips:

- In case of use to dissolve old paint layers to improve the adhesion of the subsequent coating: Spot blender must be applied uniformly on the old paintwork and recoated within a few minutes.
- In case of use as a fade-out thinner: after application of the main product, immediately spray Spot blender over the border areas (overspray areas). Cover the overspray edges with a uniform coat of Spot blender until the rough overspray becomes visibly smooth. Do not apply too much, otherwise irregular dissolving or runs are to be expected.

ATTENTION

- Test suitability to avoid unwanted wrinkling/raising of old paintwork
- Do not apply on thermoplastic substrates



CHAMÄLEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAMÄLEON GMBH
RUDOLF-DIESEL-STRASSE 8A
69115 HEIDELBERG
GERMANY

FON 0049 (0) 6221 - 520 440
FAX 0049 (0) 6221 - 520 449
MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

- **Shelf life:**
36 months, if stored in tightly closed original containers

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical Data Sheet, please contact the supplier via:
info@chamaeleon-produktion.de

For safety information, please refer to the corresponding Safety Data Sheet.