

TECHNICAL DATA SHEET

Revision date: 10.04.2025

AEROSOL PAINT REMOVER

Article number:	26730									
Colour:	transparent									
Intended use:	Car refinishing product/ Paint remover									
General characteristics:	<p>Effective paint remover designed to strip old paint from a wide range of surfaces. Thick gel formula clings easily to vertical areas for maximum effectiveness</p> <ul style="list-style-type: none">▪ wide spray pattern (approx.8 cm)▪ user-friendly <p>Substrates:</p> <table><tr><td>▪ wood</td><td>▪ clinker</td><td>▪ tarmac</td></tr><tr><td>▪ glass</td><td>▪ stone</td><td>▪ metal</td></tr><tr><td>▪ brickwork</td><td>▪ concrete</td><td>▪ asphalt</td></tr></table>	▪ wood	▪ clinker	▪ tarmac	▪ glass	▪ stone	▪ metal	▪ brickwork	▪ concrete	▪ asphalt
▪ wood	▪ clinker	▪ tarmac								
▪ glass	▪ stone	▪ metal								
▪ brickwork	▪ concrete	▪ asphalt								

TECHNICAL CHARACTERISTICS

Base: methylal**Smell:** solvent**Consumption:** approx. 0.8 m² (400 ml)

APPLICATION PROCESS

Before use, carefully read and observe the warning texts on the label!

Processing conditions:

Please only use in an adequate ventilated environment with an ample supply of fresh air. Processing temperature should be from +10 °C to +25 °C and max. air humidity should not exceed 80%.

Processing tips:

- Beforehand, mask the parts that shouldn't be painted
- Wear a respirator (type A2/P3 is recommended)

- The aerosol should have room temperature
- Before use, shake the aerosol for 2 min and spray a sample
- Apply Paint remover generously and allow to take effect. The time to take effect depends on the quality and age of the lacquer to be removed.
- Once softened, remove using a suitable tool
- Repeat the process if necessary
- Clean the valve after use (turn aerosol upside down and press the nozzle for approximately 5 sec)

VOC regulation:

EU limit value: Category B/e 840 g/l

This product contains max 590.2 g/l VOC

Shelf life:

120 months, if stored in tightly closed original containers.

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical Data Sheet, please contact the supplier under:

e-mail: info@chamaeleon-produktion.de

For safety information, please refer to the corresponding Safety Data Sheet.