

SAFETY DATA SHEET*in accordance with Regulation REACH regulation (EC) n° 1907/2006 - n° 2020/878**Revision date: 09.05.2022***1- IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/
UNDERTAKING****Product details****Trade name:** Aerosol chrome effect**Article number:** 26725**Relevant identified uses of the substance or mixture and uses advised against:**

Chromium plating silver paint for “do it yourself” and professional use

Sector of Use:

SU 21 Consumer uses: Families = general population = consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category: PC9a Coatings and paints, thinners, paint removers**Process category:** PROC11 Non industrial spraying**Environmental release category:**

ERC8a Wide dispersive indoor use of processing aids in open systems

ERC8d Wide dispersive outdoor use of processing aids in open systems

Intended use: Car refinishing Product/ Paint**Manufacturer/Supplier:**

Chamäleon GmbH

Rudolf-Diesel-Straße, 8a, 69115 Heidelberg

Germany

Further information obtainable from: Product Safety Department**Information in case of emergency:** + 49 70024112112 (CH)**2 – HAZARDS IDENTIFICATION****Classification of the substance or mixture****Classification according to Regulation (EC) No 1272/2008**

GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.

Label elements**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the CLP regulation.

Hazard pictograms

GHS02 GHS07

Signal word Danger**Contain:**

acetone
n-butyl acetate

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P251 Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P271 Use only outdoors or in a well-ventilated area.

P260 Do not breathe mist/vapours/spray.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313 If eye irritation persists: Get medical advice/attention.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Other hazards:

When the aerosol containers are under pressure and heated to temperatures exceeding 50 °C, they will

- deform themselves and may pose a risk of serious body injuries. The vapours are heavier than air and may form flammable and explosive mixtures with air, even at temperatures below 0 °C. High exposure, in a not well-ventilated areas, will provoke breathing difficulties, narcosis and unconsciousness
The mixture does not contains substances > = 0.1% with endocrine disrupting properties in accordance with the criteria of the Delegated Regulation (EU) 2017/2100 of the Commission or Regulation (EU) 2018/605 of the Commission.

The mixture does not contain substances classified as 'Substances of Very High Concern' (SVHC) \geq 0.1% published by the European CHemicals Agency (ECHA) under article 57 of REACH:
<http://echa.europa.eu/fr/candidate-list-table>

Results of PBT and vPvB assessment:

Accordance to Annex XIII of Regulation (EC) 1907/2006 concerning the Registration, Evaluation, Restriction of chemical substances (see section 3 and 2): does not meet the criteria for classification as PBT and vPvB therefore - not applicable.

Use according to good working practices, avoiding to disperse the product into the environment..

3- COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Description:

Substances hazardous to health or the environment , contained in concentrations equal to or in excess of exemption of EC directives or according to the criteria of REACH , or with a Community limit exposure in the workplace .

Aerosol can, under pressure with a mixture of solvents, resins, pigments, additives and propellant.

Components:		
CAS: 68476-40-4 EINECS: 270-681-9 Reg.nr.: 01-2119486557-22-XXXX	hydrocarbons, C3-C4 (propane, butane, isobutane)	>30-<40%
	Flam. Gas 1, H220; Press. Gas, H280	
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-XXXX EUH066	acetone	>10-<20%
	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 105-58-8 EINECS: 203-311-1	diethyl carbonate	>10-<20%
	Flam. Liq. 3, H226	
CAS: 1330-20-7 EINECS: 215-535-7 Reg.nr.: 01-2119488216-32-0000	Xilene (benzene <0.01%)	>5-<10%
	Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335; Aquatic Chronic 3, H412	

CAS: 7429-90-5 EINECS: 231-072-3 Reg.nr.: 01-2119529243-45-0000	aluminium powder (stabilized)	>1-<2.5%
	Flam. Sol. 1, H228	
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29-XXXX EUH066	n-butyl acetate	>1-<2.5%
	Flam. Liq. 3, H226; STOT SE 3, H336	

SVHC: No one SVHC present in the mixture

Additional information: Hydrocarbons C3-4 Nota K 1,3 Butadiene <0,1%

4- FIRST - AID MEASURE

Description of first aid measures

General information:

In all cases of doubt, or when symptoms of discomfort persist, seek medical attention. Never give beverages, if the person is unconscious.

After inhalation:

Immediately transport the person to an uncontaminated area. If breathing is weak or stopped apply artificial respiration and seek medical advice immediately. If the person is unconscious, take the body on the late with extension of the head, so that the eventual vomiting goes out.

After skin contact:

Remove contaminated clothes immediately. Wash off immediately with copious quantities of water for at least 10 minutes.

Do not use solvents. If irritation persists, consult a doctor

After eye contact:

Wash the eyes with copious amounts of water for 10 minutes, keeping eyelids opened. Eventually remove contact-lens.

Protect eyes with sterile gauze. Do not use drops or ointments of any kind before visiting the specialist doctor.

After swallowing:

An accidental ingestion of aerosol product is unlikely to happen. Seek medical advice immediately. Cause vomiting only if the doctor indicates to do so.

Information for doctor:

Most important symptoms and effects, both acute and delayed:

The lack of oxygen due to exposure to high concentrations may cause asphyxiation.

Danger :

Danger of impaired breathing.

Only if aspirated during the eventual swallowing it could be possible a risk of bronchial pneumonia and pulmonary oedema.

Indication of any need to immediately consult a doctor and special treatments:

- Symptomatic treatment (decontamination, vital functions).
The mixture contains volatile substances which may cause serious central nervous system depression, with effects such as drowsiness, dizziness, unconsciousness, narcosis.

5- FIRE - FIGHTING MEASURE

Extinguishing media

Suitable extinguishing agents: Dry powder, carbon dioxide or chemical foams.

Unsuitable extinguishing agents:

Direct jets of water. The fine spray of water is used to cool aerosol containers exposed to fire or heat in order to prevent bursts and explosions.

Special hazards arising from the substance or mixture:

Can be released in case of fire

Carbon monoxide (CO)

The heat causes an increase in pressure within aerosol containers, which will deform, burst and can be projected at a considerable distance, with the risk of spread of the fire. Exposure to combustion gases can lead to serious health risks.

Under certain fire conditions, traces of other toxic gases cannot be excluded.

Avoid inhalation of fumes evolved in a fire, use self-contained breathing apparatus and protective clothing, keep at a safe distance.

Advice for firefighters:

Protective equipment: Wear self-contained breathing apparatus.

Additional information:

Before approaching the fire, wear a total fire equipment, completed with a helmet visor with a protection for the neck.

6- ACCIDENTAL RELEASE MEASURE

Personal precautions, protective equipment and emergency procedures:

If the aerosol containers undergo damage that cause leaking, immediately avoid any possible point of inflammation. Do not use tools or machines that can produce sparks. Do not breathe vapours and aerosols. Provide adequate ventilation and immediately isolate the damaged aerosol containers.

Environmental precautions:

Do not allow to enter the ground/soil.

Collect the liquid phase of the product with absorbent inert material, preventing dumping into sewerage.

Ventilate the contaminated room till the gas are completely dissolved.

Methods and material for containment and cleaning up: Absorb liquid components with liquid-binding material.

Reference to other sections

- See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7- HANDLING AND STORAGE

Precautions for safe handling: Ensure good ventilation/exhaustion at the workplace.

Handling:

Handle only in well-ventilated areas. Do not use in the presence of flames or other source of possible sparkles. Do not turn on electrical appliances until the vapours are completely dispersed. see also section 8
Avoid contact with eyes.

Follow the normal hygiene rules.

Information about protection against explosions and fires:

Keep ignition sources away - Do not smoke.

Do not spray on flames or red-hot objects.

Conditions for safe storage, including any incompatibilities:

Keep the containers in the original boxes, completely avoiding the possibility of falls or collisions. Do not store in underground rooms, propellant and solvents have a significantly higher density in air. Protect from the sun's rays. Store in cool and dry place, away from sources of heat. Keep away from any source of combustion - Do not smoke. Keep away from oxidizing agents, strongly acidic or alkaline products. Store in places intended for flammable products, with appropriate ventilation and far from electrical appliances thus avoiding the accumulation of electrostatic charges. Observe the provisions prescribed by the Fire Department, according to the quantities stored.

Storage: Store the packaging on solid structures.

Specific end use(s):

The product is of general use for paint touch-up or limited areas. The safety advice to prevent P271 is to use only outdoors or in a well ventilated area.

8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Values threshold limits exposure of ingredients ACGIH TLV - TWA (Time Weighted Average) for 8 h and TLV STEL (Short-Term Exposure Limit) for 15 min.

Components with limit values that require monitoring at the workplace:	
68476-40-4 hydrocarbons, C3-C4 (propane, butane, isobutane)	
WEL	Long-term value: 1000 ppm
67-64-1 acetone	

WEL	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm	
1330-20-7 Xilene (benzene <0.01%)		
WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk, BMGV	
123-86-4 n-butyl acetate		
WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm	
Biological limit value - DNEL		
68476-40-4 hydrocarbons, C3-C4 (propane, butane, isobutane)		
Inhalative	DNEL(GLOB)	16000 mg/m ³ (rats) (OECD Guideline 422 EPA OPPTS 870.3650) Huntingdon Life Sciences (HLS) (2010a)
67-64-1 acetone		
Dermal	DNEL (EC)	62 mg/kg (Long term - Dermal - Population)
	DNEL/24h	186 mg/kg (Long term - Dermal - Workers)
Inhalative	DNEL (EC)	1210 mg/m ³ (Long term - Inhalation - Workers)
		200 mg/m ³ (long-term population)
	DNEL/24h	2400 mg/m ³ (Short term - Inhalation - Workers)
1330-20-7 Xilene (benzene <0.01%)		
Inhalative	DNEL (EC)	289 mg/m ³ (Short term - Inhalation - Workers)
		77 mg/m ³ (Long term - Inhalation - Workers)
		14.8 mg/m ³ (long-term population)
123-86-4 n-butyl acetate		
Inhalative	DNEL (EC)	480 mg/m ³ (Long term - Inhalation - Workers)
		102 mg/m ³ (long-term population)
	DNEL/24h	960 mg/m ³ (Short term - Inhalation - Workers)

Biological limit value - PNEC		
67-64-1 acetone		
PNEC STP (EC)	100 mg/L (purification plant)	
PNEC (EC)	10.6 mg/L (fresh-water)	
	1.06 mg/L (sea-water)	
	21 mg/L (émissions occasionnelles)	
	30.4 mg/kg (sediment (freshwater))	
	3.04 mg/kg (sediment (sea water))	
	33.3 mg/kg (soil)	
1330-20-7 Xilene (benzene <0.01%)		

PNEC (EC)	0.327 mg/L (fresh-water) 0.327 mg/L (sea-water) 12.46 mg/kg (sea-water) 0.327 mg/L (occasional emission) 12.46 mg/kg (sediment (freshwater)) 2.31 mg/kg (soil)
-----------	---

Ingredients with biological limit values:	
67-64-1 acetone	
IBE	50 mg/l Medium: urine Sampling time: ft Parameter: acetone
1330-20-7 Xilene (benzene <0.01%)	
BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

Additional information:

The particle diameter of the preparation are less than 100 microns; a part of these, indicatively 1% by weight, is less than 10 microns. The mass aerodynamic diameter is 28 microns. These values are, however, vary according to temperature, time of delivery and use patterns.

Exposure controls:

Avoid inhaling gas, vapours and aerosol particles, using a properly ventilated environment, in order to maintain the concentration below the exposure limits.

If the measures of environmental hygiene are not enough to fall below these limits, appropriate respiratory protection must be adopted.

General protective and hygienic measures:

The usual precautionary measures should be adhered to general rules for handling chemicals.

Keep away from foodstuffs, beverages and food.

Take off immediately all contaminated clothing

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Breathing equipment:

Not necessary if room is well-ventilated.

If exposure limits are exceeded, use a full face mask with filter gases, organic vapours and dust, type EN141 & EN143 & EN371

Protection of hands:

In case of prolonged usage, use protective gloves resistant to solvents, such as neoprene or PVA, type EN374

- Eye protection:**
 Wear security glasses whenever there is a possibility of contact with the product.
 Gauze goggles EN 166 CE.
 Glasses of hermetic protection, resistance to solvents, with side protection, type EN166.
- Body protection:**
 In case of correct use not necessary.
 Antistatic shoes and clothing.

9 – PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties	
General Information	
Appearance:	
Form:	<i>Can under pressure with product and liquefied gas</i>
Colour:	<i>In accordance with the product designation</i>
Odour:	<i>Solvent-like</i>
Odour threshold:	<i>Not determined.</i>
Important informations on protection of environment and on safety:	
	<i>VALUE/RANGE UNIT METHOD</i>
pH-value:	<i>Not applicable to the preparation</i>
Change in condition	
Melting point/Melting range:	<i>Not determined</i>
Boiling point/Boiling range:	<i>< 0 °C</i>
Flash point:	<i>< 0 °C</i>
Chemical heat of combustion:	<i>Superior a 20 kJ/g</i>
Inflammability	
(Directive 2008/47/EEC - 08/04/2008):	<i>Extremely flammable</i>
Decomposition temperature:	<i>Not determined.</i>
Self-inflammability:	<i>> 300 °C</i>
Danger of explosion:	<i>Superiore a 300 °C</i>
Danger of explosion:	<i>Not determined.</i>
Critical values for explosion:	
Lower:	<i>1.9 Vol % (LEL)</i>
Upper:	<i>15.0 Vol % (UEL)</i>
Pressure in the can:	<i>4,0 ± 0,2 bar at 20 °C</i>
Relative density at 20 °C:	<i>0.74 +/- 0.01 g/cm³</i>
Vapour density:	<i>Not determined.</i>
Evaporation rate:	<i>Not applicable.</i>
Solubility in / Miscibility with water:	<i>Not miscible or difficult to mix.</i>
Partition coefficient (n-octanol/water):	<i>Not determined.</i>

<p>Viscosity: dynamic: Other information: Additional information:</p>	<p><i>Not determined.</i> <i>Radioactivity: not radioactive</i> <i>The product is not explosive; however the heaviest steams could create explosive mixture in the passages and in the pipes of aeration. Then the product could take fire in presence of free flames, incandescent masses, electric motors, sparks, accumulation of static electricity or different ignition sources even if located far from the point of use.</i></p>
---	--

10- STABILITY AND REACTIVITY

Reactivity: No dangerous reaction if properly used and stored.

Chemical stability: stable if not heated to temperatures exceeding 50 °C.

Thermal decomposition / conditions to be avoided: No decomposition if used and stored according to specifications.

Possibility of hazardous reactions: No dangerous reaction if properly used and stored.

Conditions to avoid:

Avoid collisions with pointed objects and avoid falls, which causes perforations or breakage of aerosol containers and consequently spillage of gas and flammable solvents. Avoid exposure to high temperatures or direct sunlight; the heat at temperatures higher than 50 °C, which can cause the outbreak and the projection of the container, even at considerable distances, with the risk of spreading fire

Incompatible materials:

Keep away from oxidizing agents, strong acids and strong alkalis, in order to prevent corrosion of the steel containers

Hazardous decomposition products:

Carbon monoxide and carbon dioxide

The product is flammable, burning can give rise to the formation of dangerous decomposition products. see point 5

11- TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity:

LD/LC50 values relevant for classification:

68476-40-4 hydrocarbons, C3-C4 (propane, butane, isobutane)

Inhalative	LC50/¼h	14442738 mg/m ³ (rats) Clark DG and Tiston (1982) 1443 mg/L (rats) Clark DG and Tiston DJ (1982) 800000 ppm (rats) Clark DG and Tiston (1982)
	NOAEC/390h	10000 ppm (rats) (OECD Guideline 413 EPA OPPTS 870.3465 (90)) Huntingdon Life Sciences (HLS) (2009b)
67-64-1 acetone		
Oral	LD50	5800 mg/kg (rats)
Dermal	LD50	>20000 mg/kg (rabbits)
Inhalative	LC50/4h	>50 mg/L (rats)
1330-20-7 Xilene (benzene <0.01%)		
Oral	LD50	5267 mg/kg (mouse)
Dermal	LD50	>5000 mL/Kg (rabbits)
Inhalative	LC50/4h	20 mg/L (rats)
7429-90-5 aluminium powder (stabilized)		
Inhalative	LC50/4h	5 mg/L (rats)
123-86-4 n-butyl acetate		
Oral	LD50	>6400 mg/kg (rats)
Dermal	LD50	>5000 mg/kg (rabbits)
Inhalative	LC50/4h	21 mg/L (rats)

Primary irritant effect:
- on the skin:

Prolonged or repeated contacts with the skin causes the removal of the natural fats and can cause the onset of allergic no contact dermatitis.

- on the eye:

Direct contact causes serious irritation. Symptoms may include: tearing, redness, swelling and pain. Irritant effect.

Sensitization: No sensitizing effect is known.

Inhalation:

Inhalation of high concentrations of organic solvents can cause irritation to the mucous membranes and causes harmful effects to the liver, kidney and nervous system. Symptoms can include headache, dizziness, nausea, muscle weakness, fainting and, in extreme cases, loss of consciousness. Extended exposure to vapours and fogs can lead to irritations of the breathing apparatus.

Swallowing:

The accidental ingestion of aerosol is an unlikely event. Ingestion gives irritation to the throat, the digestive system, nausea, vomiting and diarrhoea. The effects may include those described for inhalation. No risk under normal conditions of use.

Only if aspirated during the eventual swallowing it could be possible a risk of bronchial pneumonia and

- pulmonary oedema.

Subacute to chronic toxicity:

Not classified. The product does not meet the classification criteria for the following hazard classes:
Acute and chronic toxicity - Specific target organ toxicity (STOT SE 1-2) single exposure - Specific target organ toxicity (STOT RE 1-2) repeated exposure

Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EC Classification Guidelines for Preparations as issued in the latest version:

Irritant

Sensitisation: Not classified. Based on available data, the product does not meet the classification criteria.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction):

Not classified. The product does not meet the classification criteria for Carcinogenicity - Mutagenicity - Reproductive Toxicity

12 – ECOLOGICAL INFORMATION

Use according to good working practices, avoiding to disperse the product into the environment.

Toxicity

Aquatic toxicity:	
68476-40-4 hydrocarbons, C3-C4 (propane, butane, isobutane)	
IC50	16000 mg/L (rats) (OECD Guideline 422 EPA OPPTS 870.3650) Huntingdon Life Sciences (HLS) (2010a)
LC50/48h	14.22 mg/L (Daphnia) USEPA OPP 2008
LC50/96h	24.11 mg/L (fish) QSAR EPA 2008
67-64-1 acetone	
EC50/96h	302 mg/L (Algae)
LC50/336h	4042 mg/L (fish)
LC50/48h	1680 mg/L (Daphnia)
1330-20-7 Xilene (benzene <0.01%)	
EC50/24h	1 mg/L (Daphnia Magna)
EC50/72h	4.36 mg/L (Pseudokirchneriella subcapitata)
LC50	2.6 mg/L (Oncortynchus mykiss)
NOEL/168h	1.57 mg/L (Daphnia Magna)
NOEL/448h	1.3 mg/L (Oncortynchus mykiss)
NOEL/72h	0.44 mg/L (Pseudokirchneriella subcapitata)

123-86-4 n-butyl acetate	
EC50/48h	44 mg/L (Daphnia Magna)
LC50/96h	18 mg/L (Pimephales promelas)

Persistence and degradability:

The propellant and the solvents disintegrate quickly in the air with photochemical reactions. There are no data on the persistence and degradability of the mixture (for data missing on substances not yet communicated by our Suppliers)

Bioaccumulative potential:

The propellant and the solvents have low split coefficients n-octanol/water and are not definable as bio accumulative.

Not applicable

Mobility in soil:

The propellant and the solvents are dispersed quickly in the air, without polluting of the soil. No data available on mobility in soil (due to missing data on substances not yet supplied by our suppliers)

Ecotoxic effects:

The aquatic toxicologists data of the ingredients listed in section 3, are not very high. They do not require the labelling of symbol of environmental danger and ecological risk phrases on the preparation.

Not applicable.

Additional ecological information: The amount of volatile organic compounds VOC is 545 g/l

General notes:

Do not allow product to reach ground water, water bodies or sewage system.

Danger to drinking water if even small quantities leak into soil.

Results of PBT and vPvB assessment:

According to Annex XIII of Regulation (EC) 1907/2006 concerning the Registration, Evaluation, Restriction of chemical substances (see section 3 and 2): does not meet the criteria for classification as PBT and vPvB therefore - not applicable.

Use according to good working practices, avoiding to disperse the product into the environment.

Other adverse effects: No further relevant information available.

13- DISPOSAL CONSIDERATION

Waste treatment methods:

Handle eventual residues or working defective pieces as safety rules, already described at the points 7 and 8. The storage of the containers with refuses inside shall be done in a proper and fixed area, well ventilated and away from heating sources and/or from incompatible materials (Chapter 10), protected by another additional area to contain, that must be incombustible, waterproof, unassailable by the refuses and physically divided from the raw materials warehouse.

Waste disposal key number:

EWC waste code referring to the empty spray cans : 15 01 10*

Code packaging Ferrous packaging code CER 15.01.04

- Code packaging Plastic caps: CER 15.01.02
EWC European waste catalogue code reported to the mixture or substance:
According to the European Waste Catalogue, Waste Codes are not specific to the article, but application specific. Waste codes should be assigned according to the application that was made of this article.
Features danger refusal:
HP3 = Flammable.
HP4 = Irritant
Uncleaned packagings:
Recommendation:
Disposal must be made according to official regulations.
The individual aerosol tin can be removed through the differentiated collection of the town solid refuses, in accordance with the rules of the interested Municipalities

14- TRANSPORT INFORMATION

UN-Number

ADR, IMDG, IATA UN1950

UN proper shipping name

ADR 1950 AEROSOLS
IMDG AEROSOLS
IATA AEROSOLS, flammable

Transport hazard class(es)

ADR



Class 2 5F Gases.
Label 2.1

IMDG, IATA



Class	2.1
Label	2.1
Packing group ADR, IMDG, IATA	Is not subject to the provisions.
Environmental hazards: Marine pollutant:	No
Special precautions for user Kemler Number ADR/RID: EMS Number:	Warning: Gases. - F-D,S-U
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	The aerosol products, packed limited quantities LQ2, under Chapter ADR 3.4 paragraphs 3.4.1.2 and 3.4.6. are in exemption ADR/RID and 2012.
ADR Limited quantities (LQ) Transport category Tunnel restriction code	1L 2 D
UN "Model Regulation": EU Regulation 927/2012 - number of Customs code:	UN1950, AEROSOLS, 2.1 3208 20 90

15 – REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations:

Other regulations, limitations and prohibitive regulations

Substances of very high concern (SVHC) according to REACH, Article 57 - 59:

Are not present substances SVHC listed in " CANDIDATE LIST "

RoHS regulation :

There are no substances: Lead, Mercury, Cadmium, hexavalent Chromim. Polybrominated biphenyls (PBB), Polybrominated diphenyl ethers (PBDEs) that are listed in the Legislative Decree of March 4, 2014 No. 27 implementing

Directive 2011/65/CE (Rohs)

Further reference provisions:

- Directive 2008/47/EEC aerosols
Regulation 1907/2006/EEC (REACH)
Regulation 1272/2008/EEC (CLP/GHS)
Regulation 790/2009/EEC
Regulation (UE) N. 453/2010 - 20/05/2010

Chemical safety assessment:

Exposure scenarios for substances are available which lead to the classification of the mixture.
A Chemical Safety Assessment has not been carried out.

16-OTHER INFORMATION**Relevant phrases**

H220 Extremely flammable gas.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H228 Flammable solid.
H280 Contains gas under pressure; may explode if heated.
H304 May be fatal if swallowed and enters airways.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H412 Harmful to aquatic life with long lasting effects.

Training hints: The training of workers on chemical agents must be conducted in accordance with Directive No. 98/24/EC.

Recommended restriction of use:

The information have been filled out to the best of our knowledge on the basis of the National and European regulations.

The consumer has the responsibility of using the product, according to the instructions and of taking all the necessary measures for to comply with the laws and local rules regarding security and hygiene of the work and conservation of the environment. The information given must be considered as a description of the security demanded relative to our product.

We decline any responsibility for the consequent damages due to improper usage of the product.

Abbreviations and acronyms:

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)
ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

- IMDG: International Maritime Code for Dangerous Goods
- IATA: International Air Transport Association
- GHS: Globally Harmonized System of Classification and Labelling of Chemicals
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- VOC: Volatile Organic Compounds (USA, EU) (=COV)
- DNEL: Derived No-Effect Level (REACH)
- PNEC: Predicted No-Effect Concentration (REACH)
- LC50: Lethal Concentration in atmosphere for 50% of animal test.
- LD50: Lethal dose for 50% test animal
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent and very Bioaccumulative
- STEL: Short Term Exposure Limit
- TLV: Theshold Limit Value
- TWA: Time Weighted Average
- PBT: Persistent, Bioaccumulative and Toxic
- vPvB: very Persistent very Bioaccumulative
- CLP: Classification, Labelling and Packaging
- REACH: Registration, Evalutation, Authorization of CHemicals
- SVHC : Substance of Very High Concern
- PNEC: Predicted No Effect Concentration (Risk Assesment)
- ACGIH: American Conference of Governmental Industrial Hygienists.
- STEL/C: Short-Term Exposure Limit/Ceiling.
- LEL: Lower Explosive Limit
- UEL: Upper Explosive Limit
- BW: Body weight
- NOAEL: No Observed Adverse Effects Level
- RoHS: Restriction on the use of Hazardous Substances.
- RTECS : Registry of Toxic Effects of Chemical Substances.
- NOAEC : No Observed Adverse Effects Concentratin
- CER : Catalogo Europeo Rifiuti.
- NOAEL : No Observed Adverse Effects Concentration
- Flam. Sol. 1: Flammable solids, Hazard Category 1
- Acute Tox. 4: Acute toxicity, Hazard Category 4
- Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
- STOT RE 2: Specific target organ toxicity - Repeated exposure, Hazard Category 2
- Asp. Tox. 1: Aspiration hazard, Hazard Category 1
- Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 3

The information contained in these sheets is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.