

SAFETY DATA SHEET
according to 1907/2006/EC, Article 31

Revision date: 20.06.2023

**1- IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/
UNDERTAKING**

Product details

Trade name: Aluminium putty

Article number: 15042, 15044, 15045, 15046, 15049

Relevant identified uses of the substance or mixture and uses advised against:

No further relevant information available.

Intended use: Car refinishing product/Knife filler/ Surfacer

Manufacturer/Supplier:

Chamäleon GmbH

Rudolf-Diesel-Straße, 8a, 69115 Heidelberg

Germany

Further information obtainable from: Product Safety Department

Information in case of emergency: + 49 70024112112 (CH)

2 – HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



health hazard

Repr. 2 H361d Suspected of damaging the unborn child.

STOT RE 1 H372 Causes damage to the hearing organs through prolonged or repeated exposure.



Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2 H319 Causes serious eye irritation.
Skin Sens. 1 H317 May cause an allergic skin reaction.

Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GP CLP regulation.

Hazard pictograms



GHS02 GHS07 GHS08

Signal word Danger

Hazard-determining components of labelling:

Styrene

Maleic anhydride

2,2'-(m-Tolylimino)diethanol

Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl](4-methylphenyl)amino]-

Hazard statements

H226 Flammable liquid and vapour.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H361d Suspected of damaging the unborn child.

H372 Causes damage to the hearing organs through prolonged or repeated exposure.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P403+P235 Store in a well-ventilated place. Keep cool.

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

3- COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 100-42-5 EINECS: 202-851-5 Reg.nr.: 01-2119457861-32	styrene Flam. Liq. 3, H226 Repr. 2, H361d; STOT RE 1, H372; Asp. Tox. 1, H304 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 Aquatic Chronic 3, H412	≥10-≤20%
CAS: 7429-90-5 EINECS: 231-072-3 Reg.nr.: 01-2119529243-45	aluminium powder (stabilized)/ manufacturer Flam. Sol. 1, H228	<2.5%
CAS: 91-99-6 EINECS: 202-114-8	2,2'-(m-Tolylimino)diethanol STOT RE 2, H373; Eye Dam. 1, H318; dAcute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1B, H317	≥0.1-<1%
EC number: 911-490-9	Reaction mass of 2,2'-[(4-methylphenyl)imino]bisethanol and Ethanol 2-[[2-(2-hydroxyethoxy)ethyl] (4-methylphenyl) amino]- Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Irrit. 2, H315; Skin Sens. 1, H317; Aquatic Chronic 3, H412	≥0.1-<1%
CAS: 108-31-6 EINECS: 203-571-6 Reg.nr.: 01-2119472428-31	Maleic anhydride Resp. Sens. 1, H334; STOT RE 1, H372; Skin Corr. 1B, H314; Eye Dam. 1, H318; Acute Tox. 4, H302; Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.001	≥0.001- <0.1%

Additional information:

For the wording of the listed hazard phrases refer to section 16.

4- FIRST - AID MEASURE

Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately rinse with water.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: If symptoms persist consult doctor.

Most important symptoms and effects, both acute and delayed No further relevant information available. **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5- FIRE - FIGHTING MEASURE

Extinguishing media**Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

Special hazards arising from the substance or mixture:

During heating or in case of fire poisonous gases are produced.

Advice for firefighters

Protective equipment: Mouth respiratory protective device.

6- ACCIDENTAL RELEASE MEASURE

Personal precautions, protective equipment and emergency procedures:

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Environmental precautions: Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections:

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7- HANDLING AND STORAGE

Precautions for safe handling:

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: No special requirements.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions: Keep container tightly sealed.

Storage class: 3

Specific end use(s): No further relevant information available.

8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Ingredients with limit values that require monitoring at the workplace:	
100-42-5 styrene	
WEL	Short-term value: 1080 mg/m ³ , 250 ppm Long-term value: 430 mg/m ³ , 100 ppm
7429-90-5 aluminium powder (stabilized)/ manufacturer classification	
WEL	Long-term value: 10* 4** mg/m ³ *inhalable dust **respirable dust
108-31-6 Maleic anhydride	
WEL	Short-term value: 3 mg/m ³ Long-term value: 1 mg/m ³ Sen

Additional information: The lists valid during the making were used as basis.

Exposure controls

Appropriate engineering controls: No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Breakthrough time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye/face protection

Tightly sealed goggles

9 – PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties	
General Information	
Physical state	Fluid
Colour:	According to product specification
Odour:	Characteristic
Odour threshold:	Not determined.
Melting point/freezing point:	Undetermined.
Boiling point or initial boiling point and boiling range:	145.2 °C (100-42-5 Styrene)
Flammability:	Flammable.
Lower and upper explosion limit	
Lower:	1.2 Vol % (100-42-5 Styrene)

Upper:	8.9 Vol % (100-42-5 Styrene)
Flash point:	31 °C (DIN EN ISO 1523:2002)
Auto-ignition temperature:	480 °C (DIN 51794, 100-42-5 Styrene)
Decomposition temperature:	Not determined.
pH:	Not determined.
Viscosity:	
Kinematic viscosity:	Not determined.
Dynamic at 20 °C:	77,000 mPas
Solubility	
water:	Not miscible or difficult to mix.
Partition coefficient n-octanol/water (log value):	Not determined.
Vapour pressure at 20 °C:	6 hPa (100-42-5 Styrene)
Vapour pressure at 50 °C:	35 hPa
Density and/or relative density	
Density at 20 °C:	1.735 g/cm ³ (DIN EN ISO 2811-1)
Relative density	Not determined.
Vapour density	Not determined.
Other information	
Appearance:	
Form:	Fluid
Important information on protection of health and environment, and on safety.	
Ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Solvent content:	
VOC (EC)	1,45%
Solids content (weight-%):	83.3 %
Change in condition	
Evaporation rate:	Not determined.
Information with regard to physical hazard classes	
Explosives:	Void
Flammable gases:	Void
Aerosols:	Void
Oxidising gases:	Void

Gases under pressure:	Void
Flammable liquids:	Flammable liquid and vapour.
Flammable solids:	Void
Self-reactive substances and mixtures:	Void
Pyrophoric liquids:	Void
Pyrophoric solids:	Void
Self-heating substances and mixtures:	Void
Substances and mixtures, which emit flammable gases in contact with water:	Void
Oxidising liquids:	Void
Oxidising solids:	Void
Organic peroxides:	Void
Corrosive to metals:	Void
Desensitised explosives:	Void

10- STABILITY AND REACTIVITY

Reactivity No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions: No dangerous reactions known.

Conditions to avoid: No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: Carbon monoxide.

11- TOXICOLOGICAL INFORMATION

Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity Based on available data, the classification criteria are not met.

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/irritation: Causes serious eye irritation.

Respiratory or skin sensitisation: May cause an allergic skin reaction.

Reproductive toxicity: Suspected of damaging the unborn child.

STOT-repeated exposure: Causes damage to the hearing organs through prolonged or repeated exposure.

12 – ECOLOGICAL INFORMATION

Toxicity

Aquatic toxicity: No further relevant information available.

Persistence and degradability: No further relevant information available.

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Endocrine disrupting properties:

For information on endocrine disrupting properties see section 11.

Other adverse effects

Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) : hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

13– DISPOSAL CONSIDERATION

Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations.

14– TRANSPORT INFORMATION

UN number or ID number

ADR, IMDG, IATA

UN3269

UN proper shipping name

ADR

IMDG, IATA

UN3269 POLYESTER RESIN KIT

POLYESTER RESIN KIT

Transport hazard class(es)
ADR



Class 3 (F3) Flammable liquids.
Label 3

IMDG, IATA



Class 3 Flammable liquids.
Label 3

Packing group
ADR, IMDG, IATA

III

Environmental hazards:

Marine pollutant: No

Special precautions for user Warning: Flammable liquids.

Hazard identification number (Kemler code): -

EMS Number: F-E,S-D

Stowage Category A

Maritime transport in bulk according to IMO

Instruments: Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ) 5L

Transport category 3

Tunnel restriction code E

IMDG

Limited quantities (LQ) 5L

UN "Model Regulation": UN 3269 POLYESTER RESIN KIT, 3, III

15 – REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture.

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5000 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 50000 t

National regulations:

Additional classification according to Decree on Hazardous Materials, Annex II:

Class	Share in %
NK	10-25

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16-OTHER INFORMATION

Relevant phrases

H226 Flammable liquid and vapour.

H228 Flammable solid.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation.

H361d Suspected of damaging the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Flam. Sol. 1: Flammable solids – Category 1

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1B: Skin corrosion/irritation – Category 1B

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Skin Sens. 1B: Skin sensitisation – Category 1B

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

The information contained in these sheets is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.