

SAFETY DATA SHEET
according to 1907/2006/EC, Article 31

Revision date: 03.06.2022

**1- IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/
UNDERTAKING**

Product details

Trade name: 2K Epoxy primer

Article number: 14013

Relevant identified uses of the substance or mixture and uses advised against:

No further relevant information available.

Sector of Use:

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

SU21 Consumer uses: Private households / general public / consumers

Product category: PC9a Coatings and paints, thinners, paint removers

Process category:

PROC7 Industrial spraying

PROC11 Non industrial spraying

Intended use: Car refinishing product/ Lacquer

Manufacturer/Supplier:

Chamäleon GmbH

Rudolf-Diesel-Straße 8a,

69115 Heidelberg

Germany

Further information obtainable from: Product Safety Department

Information in case of emergency: + 49 70024112112 (CH)

2 – HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



health hazard

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02 GHS07 GHS08

Signal word Danger

Hazard-determining components of labelling:

reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700-1000)
xylene

Condensation products of dimerised fatty acids, C18-unsaturated, with N,N-dimethyl-1,3-propanediamine
and 1,3-propanediamine

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P280 Wear protective gloves / eye protection.

P284 In case of inadequate ventilation wear respiratory protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P312 Call a POISON CENTER/doctor if you feel unwell.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

Additional information:

Buildup of explosive mixtures possible without sufficient ventilation.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

3- COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37	dimethyl ether Flam. Gas 1A, H220 Press. Gas (Comp.), H280	25-<50%
EC number: 905-588-0 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32	xylene Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	12.5-<20%
CAS: 25068-38-6 NLP: 500-033-5 Index number: 603-074-00-8 Reg.nr.: 01-2119456619-26	reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight = 700-1000) Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317	5-<10%
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	acetone Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	5-<10%
CAS: 107-98-2 EINECS: 203-539-1	1-methoxy-2-propanol	2.5-<5%

Index number: 603-064-00-3 Reg.nr.: 01-2119457435-35	Flam. Liq. 3, H226 STOT SE 3, H336	
EC number: 918-668-5 Reg.nr.: 01-2119455851-35	Hydrocarbons, C9, aromatics Flam. Liq. 3, H226 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 STOT SE 3, H335-H336 EUH066	<2.5%
CAS: 108-94-1 EINECS: 203-631-1 Index number: 606-010-00-7 Reg.nr.: 01-2119453616-35	cyclohexanone Flam. Liq. 3, H226 Eye Dam. 1, H318 Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	<2.5%
CAS: 13463-67-7 EINECS: 236-675-5 Index number: 022-006-00-2 Reg.nr.: 01-2119489379-17	titanium dioxide Carc. 2, H351	<2.5%
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate Flam. Liq. 3, H226 STOT SE 3, H336	<2.5%
CAS: 7779-90-0 EINECS: 231-944-3 Index number: 030-011-00-6 Reg.nr.: 01-2119485044-40	trizinc bis(orthophosphate) Aquatic Acute 1, H400; Aquatic Chronic 1, H410	≤0.5%
CAS: 162627-17-0 EC number: 605-296-0 Reg.nr.: 01-2119970640-38-XXXX	Condensation products of dimerised fatty acids, C18-unsaturated, with N,N-dimethyl-1,3-propanediamine and 1,3-propanediamine Skin Sens. 1, H317	≤0.5%

Additional information:

The content of Benzene (EINECS-Nr. 200-753-7) in the ingredients is less than 0,1% (Note P Annex 1A 1272/2008 EU), so the classification as carcinogen need not to apply.

xylene: Contains ethylbenzene CAS 100-41-4

For the wording of the listed hazard phrases refer to section 16.

4- FIRST - AID MEASURES

Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

Most important symptoms and effects, both acute and delayed: No further relevant information available.

Indication of any immediate medical attention and special treatment needed:

No further relevant information available.

5- FIRE - FIGHTING MEASURES

Extinguishing media

Suitable extinguishing agents:

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

Special hazards arising from the substance or mixture:

During heating or in case of fire poisonous gases are produced.

Advice for firefighters -

Protective equipment: Mouth respiratory protective device.

6- ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

- Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Reference to other sections
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7- HANDLING AND STORAGE

Precautions for safe handling: Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke

Keep respiratory protective device available.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep container tightly sealed.

Storage class: 2B

Specific end use(s): No further relevant information available.

8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Ingredients with limit values that require monitoring at the workplace:	
115-10-6 dimethyl ether	
WEL	Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm
xylene	
WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
67-64-1 acetone	
WEL	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm

107-98-2 1-methoxy-2-propanol	
WEL	Short-term value: 560 mg/m ³ , 150 ppm Long-term value: 375 mg/m ³ , 100 ppm Sk
13463-67-7 titanium dioxide	
WEL	Long-term value: 10* 4** mg/m ³ *total inhalable **respirable
108-65-6 2-methoxy-1-methylethyl acetate	
WEL	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
Ingredients with biological limit values:	
xylene	
BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
108-94-1 cyclohexanone	
BMGV	2 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: cyclohexanol

Additional information: The lists valid during the making were used as basis.

Exposure controls

Appropriate engineering controls: No further data; see item 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Avoid contact with the eyes.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

Hand protection: Protective gloves

Material of gloves: Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material:

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

Eye/face protection: Tightly sealed goggles

9 – PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

General Information

Physical state:	<i>Aerosol</i>
Colour:	<i>According to product specification</i>
Odour:	<i>Characteristic</i>
Odour threshold:	<i>Not determined.</i>
Melting point/freezing point:	<i>Undetermined.</i>
Boiling point or initial boiling point and boiling range:	<i>Not applicable, as aerosol.</i>
Flammability:	<i>Not applicable.</i>
Lower and upper explosion limit	
Lower:	<i>1 Vol % (xylene)</i>
Upper:	<i>26.2 Vol % (115-10-6 dimethyl ether)</i>
Flash point:	<i>Not applicable, as aerosol.</i>
Ignition temperature:	<i>240 °C (464 °F)</i>
Decomposition temperature:	<i>Not determined.</i>
pH:	<i>Mixture is non-soluble (in water).</i>
Viscosity:	
Kinematic viscosity	<i>Not determined.</i>
Dynamic:	<i>Not determined.</i>

Solubility	
water:	<i>Not miscible or difficult to mix.</i>
Partition coefficient n-octanol/water (log value):	<i>Not determined.</i>
Vapour pressure at 20 °C (68 °F):	<i>4000 hPa (3000.2 mm Hg) (115-10-6 dimethyl ether)</i>
Density and/or relative density	
Density at 20 °C (68 °F):	<i>1 g/cm³ (8.3 lbs/gal)</i>
Relative density:	<i>Not determined.</i>
Vapour density:	<i>Not determined.</i>
Other information	
Appearance:	
Form:	<i>Aerosol</i>
Important information on protection of health and environment, and on safety.	
Explosive properties:	<i>Not determined.</i>
Solvent content:	
Organic solvents:	<i>63.3 %</i>
VOC (EC)	<i>---</i>
	<i>632.9 g/l</i>
VOC-EU%	<i>63.29 %</i>
Solids content:	<i>30.7 %</i>
Change in condition	
Evaporation rate:	<i>Not applicable.</i>
Information with regard to physical hazard classes	
Explosives:	<i>Void</i>
Flammable gases:	<i>Void</i>
Aerosols:	<i>Extremely flammable aerosol. Pressurised container: May burst if heated.</i>
Oxidising gases:	<i>Void</i>
Gases under pressure:	<i>Void</i>
Flammable liquids:	<i>Void</i>
Flammable solids:	<i>Void</i>
Self-reactive substances and mixtures:	<i>Void</i>
Pyrophoric liquids:	<i>Void</i>
Pyrophoric solids:	<i>Void</i>
Self-heating substances and mixtures:	<i>Void</i>
Substances and mixtures, which emit flammable gases in contact with water:	<i>Void</i>
Oxidising liquids:	<i>Void</i>
Oxidising solids:	<i>Void</i>
Organic peroxides:	<i>Void</i>

Corrosive to metals:	<i>Void</i>
Desensitised explosives:	<i>Void</i>

10- STABILITY AND REACTIVITY

Reactivity No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: No dangerous decomposition products known.

11- TOXICOLOGICAL INFORMATION

Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

LD/LC50 values relevant for classification:		
xylene		
Oral	LD50	3523 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	29000 mg/m ³ (rat)
67-64-1 acetone		
Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	>15800 mg/kg (rabbit)
Inhalative	LC50/4 h	76 mg/l (rat)
Hydrocarbons, C9, aromatics		
Oral	LD50	>5000 mg/kg (rat) (OECD 401)
Dermal	LD50	>2000 mg/kg (rab) (OECD 402)
108-94-1 cyclohexanone		
Inhalative	LC50/4 h	6.2 mg/l (rat)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	8530 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50/4 h	>10000 mg/m ³ (rat)

Skin corrosion/irritation: Causes skin irritation.

Serious eye damage/irritation: Causes serious eye irritation.

Respiratory or skin sensitization: May cause an allergic skin reaction.

STOT-repeated exposure: May cause damage to organs through prolonged or repeated exposure.

Information on other hazards

Endocrine disrupting properties
None of the ingredients is listed.

12 – ECOLOGICAL INFORMATION

Toxicity

Aquatic toxicity:	
115-10-6 dimethyl ether	
EC50 / 96 h	155 mg/l (algae)
LC50 / 48 h	>4000 mg/l (daphnia magna)
LC50 / 96 h	>4000 mg/l (fish)
xylene	
EC50 / 48 h	7.4 mg/l (daphnia magna)
LC50 / 96 h	13.5 mg/l (fish)
67-64-1 acetone	
LC50/96h	8300 mg/l (fish)
EC50/96h	7200 mg/l (algae)
LC50 / 48 h	8450 mg/l (crustacean (water flea))
Hydrocarbons, C9, aromatics	
EC50 / 48 h	302 mg/l (daphnia magna)
EC50 / 72 h	2.75 mg/l (Pseudokirchneriella subcapitata)
EC50 / 96 h	9.2 mg/l (Regenbogenforelle)
108-65-6 2-methoxy-1-methylethyl acetate	
EC50 / 48 h	>500 mg/l (daphnia magna)
LC50 / 96 h	100-180 mg/l (oncorhynchus mykiss / Regenbogenforelle)

Persistence and degradability No further relevant information available.

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Endocrine disrupting properties:

The product does not contain substances with endocrine disrupting properties.



Other adverse effects

Remark: Harmful to fish

Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
Harmful to aquatic organisms

13- DISPOSAL CONSIDERATION

Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:

Recommendation: Dispose of packaging according to regulations on the disposal of packagings.

14- TRANSPORT INFORMATION

UN number or ID number

ADR, IMDG, IATA UN1950

UN proper shipping name

ADR 1950 AEROSOLS
IMDG AEROSOLS
IATA AEROSOLS, flammable

Transport hazard class(es)

ADR



Class 2 5F Gases.
Label 2.1

IMDG, IATA



Class 2.1 Gases.
Label 2.1

Packing group

ADR, IMDG, IATA not regulated

Environmental hazards:

Marine pollutant: Yes

Special precautions for user

Warning: Gases.
Hazard identification number (Kemler code): -
EMS Number: F-D,S-U
Stowage Code: SW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
Segregation Code: SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2.
For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

Maritime transport in bulk according to IMO instruments:

Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ) 1L
Excepted quantities (EQ) Code: E0
Not permitted as Excepted Quantity

Transport category

2

Tunnel restriction code

D

IMDG

Limited quantities (LQ) 1L
Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

UN "Model Regulation": UN 1950 AEROSOLS, 2.1

15 – REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture
Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P3a FLAMMABLE AEROSOLS

Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t

Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t

LIST OF SUBSTANCES SUBJECT TO AUTHORISATION (UK ANNEX XIV)

Regulation (EC) No 273/2004 on drug precursors		
67-64-1	acetone	3

National regulations:

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16-OTHER INFORMATION

Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H351 Suspected of causing cancer.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H411 Toxic to aquatic life with long lasting effects.

EUH066 Repeated exposure may cause skin dryness or cracking.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3



CHAMÄLEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAMÄLEON GMBH
RUDOLF-DIESEL-STRASSE 8A
69115 HEIDELBERG
GERMANY

FON 0049 (0) 6221 - 520 440
FAX 0049 (0) 6221 - 520 449
MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

■
The information contained in these sheets is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.