

SAFETY DATA SHEET
according to 1907/2006/EC, Article 31 *Revision date: 30.03.2022*

**1- IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/
UNDERTAKING**

Product details

Trade name: Pre-fill premium

Article number: 25005

Relevant identified uses of the substance or mixture and uses advised against:

No further relevant information available.

Sector of Use:

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

Product category: Paint remover

Process category:

PROC7 Industrial spraying

PROC11 Non industrial spraying

Intended use: Car refinishing product/ Preparation

Manufacturer/Supplier:

Chamäleon GmbH

Rudolf-Diesel-Straße, 8a

69115 Heidelberg

Germany

Further information obtainable from: Product Safety Department

Information in case of emergency: + 49 70024112112 (CH)

2 – HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Eye Irrit. 2 H319 Causes serious eye irritation.
STOT SE 3 H336 May cause drowsiness or dizziness.

Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the GB CLP regulation.

Hazard pictograms



GHS02 GHS07

Signal word Danger

Hazard-determining components of labelling:

acetone

butan-1-ol

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P260 Do not breathe spray.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents / container in accordance with regional regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Buildup of explosive mixtures possible without sufficient ventilation.

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

3- COMPOSITION/INFORMATION ON INGREDIENTS

Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37	dimethyl ether	50-<75%
	Flam. Gas 1A, H220 Press. Gas (Comp.), H280	
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 Reg.nr.: 01-2119471330-49	acetone	25-<50%
	Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336 EUH066	
EC number: 905-588-0 Reg.nr.: 01-2119488216-32-xxxx	xylene	2.5-<5%
	Flam. Liq. 3, H226 STOT RE 2, H373; Asp. Tox. 1, H304 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335	
CAS: 71-36-3 EINECS: 200-751-6 Index number: 603-004-00-6 Reg.nr.: 01-2119484630-38	butan-1-ol	<2.5%
	Flam. Liq. 3, H226 Eye Dam. 1, H318 Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	

Additional information: For the wording of the listed hazard phrases refer to section 16.

4- FIRST - AID MEASURE

Description of first aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Generally the product does not irritate the skin.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

Most important symptoms and effects, both acute and delayed

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5- FIRE - FIGHTING MEASURE

Extinguishing media

Suitable extinguishing agents: Use fire extinguishing methods suitable to surrounding conditions.

Special hazards arising from the substance or mixture

During heating or in case of fire poisonous gases are produced.

Advice for firefighters -

Protective equipment: Mouth respiratory protective device.

6- ACCIDENTAL RELEASE MEASURE

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

Keep away from ignition sources.

Environmental precautions: Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7- HANDLING AND STORAGE

Precautions for safe handling: Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility: Not required.

Further information about storage conditions: Keep container tightly sealed.

Storage class: 2 B

Specific end use(s) No further relevant information available.

8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Ingredients with limit values that require monitoring at the workplace:	
115-10-6 dimethyl ether	
WEL	Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm
67-64-1 acetone	
WEL	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm
xylene	
WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
71-36-3 butan-1-ol	
WEL	Short-term value: 154 mg/m ³ , 50 ppm Sk

DNELs		
67-64-1 acetone		
Oral	DNEL	62 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	62 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	186 mg/kg /per day (Worker, longterm systemic)
	DNEL	2420 mg/m ³ (Worker, acute local)
	DNEL	1210 mg/m ³ (Worker, longterm systemic)
	DNEL	200 mg/m ³ (Consumer, longterm systemic)
	DNEL	60 mg/m ³
xylene		

Oral	DNEL	1.6 mg/kg /per day (Consumer, longterm systemic)
Dermal	DNEL	180 mg/kg /per day (Worker, longterm systemic)
Inhalative	DNEL	211 mg/m ³ (Worker, longterm systemic)
	DNEL	221 mg/m ³ (Worker, longterm local)
	DNEL	442 mg/m ³ (Worker, acute systemic)
	DNEL	289 mg/m ³ (Worker, acute local)
	DNEL	14.8 mg/m ³ (Consumer, longterm systemic)
	DNEL	260 mg/m ³ (Consumer; acute systemic)
	DNEL	65.3 mg/m ³ (Consumer, longterm local)
	DNEL	260 mg/m ³ (Consumer, acute local)
71-36-3 butan-1-ol		
Oral	DNEL	3.125 mg/kg /per day (Consumer, longterm systemic)
Inhalative	DNEL	310 mg/m ³ (Worker, longterm local)
	DNEL	55 mg/m ³ (Consumer, longterm local)

PNECs

67-64-1 acetone

PNEC	10.6 mg/l (Freshwater)
PNEC	1.06 mg/l (Seawater)
PNEC	21 mg/l (Sporadic release)
PNEC	100 mg/l (Sewage treatment plant)
PNEC	30.4 mg/kg (Freshwater sediment)
PNEC	3.04 mg/kg (Seawater sediment)
PNEC	29.5 mg/kg (Soil)

71-36-3 butan-1-ol

PNEC	0.082 mg/l (Freshwater)
PNEC	0.0082 mg/l (Seawater)
PNEC	2.25 mg/l (Sporadic release)
PNEC	2476 mg/l (Sewage treatment plant)
PNEC	0.178 mg/kg (Freshwater sediment)
PNEC	0.0178 mg/kg (Seawater sediment)
PNEC	0.015 mg/kg (Soil)

Ingredients with biological limit values:

xylene

BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid
------	--

Additional information: The lists valid during the making were used as basis.

Exposure controls

Appropriate engineering controls: No further data; see section 7.

Individual protection measures, such as personal protective equipment

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

Avoid contact with the eyes.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Filter A2/P3

Hand protection: Protective gloves

Material of gloves

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer.

Penetration time of glove material:

Butyl rubber gloves with a thickness of 0.4 mm are resistant to:

Acetone: 480 min

Butyl acetate: 60 min

Ethyl acetate: 170 min

Xylene: 42 min

Butyl rubber gloves with a thickness of 0.4 mm are solvent resistant for 42- 480 minutes. As protective measure, we recommend that users and responsible persons for work safety assume solvent resistance length of 42 minutes. Considering the data in section 3 of this SDS, one can assume longer resistance length in particular cases.

Eye/face protection: Tightly sealed goggles

9 – PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

General Information

Physical state:	<i>Aerosol</i>
Colour:	<i>Clear</i>
Odour:	<i>Solvent-like</i>
Odour threshold:	<i>Not determined.</i>
Melting point/freezing point:	<i>Undetermined.</i>

Boiling point or initial boiling point and boiling range:	<i>Not applicable, as aerosol.</i>
Flammability:	<i>Not applicable.</i>
Lower and upper explosion limit:	
Lower:	<i>2.6 Vol % (67-64-1 acetone)</i>
Upper:	<i>26.2 Vol % (115-10-6 dimethyl ether)</i>
Flash point:	<i>Not applicable, as aerosol.</i>
Auto-ignition temperature:	<i>240 °C (464 °F) (115-10-6 dimethyl ether)</i>
Decomposition temperature:	<i>Not determined.</i>
pH:	<i>Mixture is non-soluble (in water).</i>
Viscosity:	
Kinematic viscosity:	<i>Not determined.</i>
Dynamic:	<i>Not determined.</i>
Solubility water:	<i>Not miscible or difficult to mix.</i>
Partition coefficient n-octanol/water (log value)	<i>Not determined.</i>
Vapour pressure at 20 °C (68 °F):	<i>4000 hPa (3000.2 mm Hg)</i>
Density and/or relative density	
Density at 20 °C (68 °F):	<i>0.7 g/cm³ (5.8 lbs/gal)</i>
Relative density:	<i>Not determined.</i>
Vapour density:	<i>Not determined.</i>
Other information	
Appearance:	
Form:	<i>Aerosol</i>
Important information on protection of health and environment, and on safety.	
Explosive properties:	<i>Not determined.</i>
Solvent content:	
Organic solvents:	<i>100.0 %</i>
VOC (EC)	<i>---</i>
	<i>713.0 g/l</i>
VOC-EU%	<i>100.00 %</i>
Solids content:	<i>0.0 %</i>
Change in condition	
Evaporation rate:	<i>Not applicable.</i>
Information with regard to physical hazard classes	
Explosives:	<i>Void</i>
Flammable gases:	<i>Void</i>
Aerosols:	<i>Extremely flammable aerosol. Pressurised container: May burst if heated.</i>
Oxidising gases:	<i>Void</i>
Gases under pressure:	<i>Void</i>
Flammable liquids:	<i>Void</i>

Flammable solids:	<i>Void</i>
Self-reactive substances and mixtures:	<i>Void</i>
Pyrophoric liquids:	<i>Void</i>
Pyrophoric solids:	<i>Void</i>
Self-heating substances and mixtures:	<i>Void</i>
Substances and mixtures, which emit flammable: gases in contact with water:	<i>Void</i>
Oxidising liquids:	<i>Void</i>
Oxidising solids:	<i>Void</i>
Organic peroxides:	<i>Void</i>
Corrosive to metals:	<i>Void</i>
Desensitised explosives:	<i>Void</i>

10- STABILITY AND REACTIVITY

Reactivity No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions No dangerous reactions known.

Conditions to avoid No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: No dangerous decomposition products known.

11- TOXICOLOGICAL INFORMATION

Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity: Based on available data, the classification criteria are not met:

LD/LC50 values relevant for classification:		
67-64-1 acetone		
Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	>15800 mg/kg (rabbit)
Inhalative	LC50 / 4h	76 mg/l (rat)
xylene		

Oral	LD50	3523 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50 / 4h	29000 mg/m3 (rat)
71-36-3 butan-1-ol		
Oral	LD50	2292 mg/kg (rat)
Dermal	LD50	3430 mg/kg (rabbit)
Inhalative	LC50 / 4h	17000 mg/m3 (rat)

Skin corrosion/irritation: No irritant effect.

Serious eye damage/irritation: Causes serious eye irritation.

Respiratory or skin sensitisation: No sensitising effects known.

STOT-single exposure: May cause drowsiness or dizziness.

Information on other hazards.

Endocrine disrupting properties
None of the ingredients is listed.

12 – ECOLOGICAL INFORMATION

Toxicity

Aquatic toxicity:	
115-10-6 dimethyl ether	
EC50 / 96 h	155 mg/l (algae)
LC50 / 48 h	>4000 mg/l (daphnia magna)
LC50 / 96 h	>4000 mg/l (fish)
67-64-1 acetone	
LC50 / 96h	8300 mg/l (fish)
EC50 / 96h	7200 mg/l (algae)
LC50 / 48 h	8450 mg/l (crustacean (water flea))
xylene	
EC50 / 48 h	7.4 mg/l (daphnia magna)
LC50 / 96 h	13.5 mg/l (fish)
71-36-3 butan-1-ol	
LC50 / 96 h	1376 mg/l (fish)

Persistence and degradability: No further relevant information available.

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

Results of PBT and vPvB assessment:

PBT: Not applicable.

vPvB: Not applicable.

Endocrine disrupting properties:

The product does not contain substances with endocrine disrupting properties.

Other adverse effects

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13- DISPOSAL CONSIDERATION

Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system

Uncleaned packaging:

Recommendation:

Disposal must be made according to official regulations.

Disposal must be made according to official regulations.

14- TRANSPORT INFORMATION

UN number or ID number

ADR, IMDG, IATA

UN1950

UN proper shipping name

ADR

1950 AEROSOLS

IMDG

AEROSOLS

IATA

AEROSOLS, flammable

Transport hazard class(es)

ADR



Class 2 5F Gases.
Label 2.1

IMDG, IATA



Class 2.1 Gases.
Label 2.1

Packing group
ADR, IMDG, IATA

not regulated

Environmental hazards: Not applicable.

Special precautions for user

Warning: Gases.

Hazard identification number (Kemler code): -

EMS Number: F-D,S-U

Stowage Code:

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre:
Category A. For AEROSOLS with a capacity above 1 litre:
Category B. For WASTE AEROSOLS: Category C, Clear
of living quarters.

Segregation Code:

SG69 For AEROSOLS with a maximum capacity of 1 litre:
Segregation as for class 9. Stow "separated from" class 1
except for division 1.4.

For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class 2.

**Maritime transport in bulk according to IMO
instruments:**

Not applicable.

**Transport/Additional information:
ADR**

Limited quantities (LQ)

1L

Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

Transport category

2

Tunnel restriction code

D

IMDG

Limited quantities (LQ)

1L

Excepted quantities (EQ)

Code: E0

Not permitted as Excepted Quantity

Code: E0

Not permitted as Excepted Quantity

UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

15 – REGULATORY INFORMATION**Safety, health and environmental regulations/legislation specific for the substance or mixture.****Directive 2012/18/EU****Named dangerous substances - ANNEX I** None of the ingredients is listed.**Seveso category:** P3a FLAMMABLE AEROSOLS**Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t**Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.**16-OTHER INFORMATION****Relevant phrases**

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

EUH066 Repeated exposure may cause skin dryness or cracking.

Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (UK REACH)

PNEC: Predicted No-Effect Concentration (UK REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1A: Flammable gases – Category 1A

Aerosol 1: Aerosols – Category 1

Press. Gas (Comp.): Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

The information contained in these sheets is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.