

SAFETY DATA SHEET
according to 1907/2006/EC, Article 31 *Revision date: 24.11.2015*

1- IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product details

Trade name: Spot Blender

Article number: 13405, 13408

Intended use: Car refinishing Product/ Thinner, Diluent

Manufacturer/Supplier: Chamäleon GmbH

Rudolf-Diesel-Straße, 8a, 69115 Heidelberg -- Germany

Further information obtainable from: Product Safety Department

Information in case of emergency: + 49 70024112112 (CH)

2 – HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS05 corrosion

Eye Dam. 1 H318 Causes serious eye damage.



GHS07

Acute Tox. 4 H312 Harmful in contact with skin.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Xn; Harmful

R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.

Xi; Irritant

R38-41: Irritating to skin. Risk of serious damage to eyes.

F; Highly flammable

R11: Highly flammable.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02

GHS05

GHS07

Signal word: Danger

Hazard-determining components of labelling:

cyclohexanone

2-butoxyethyl acetate

Hazard statements

H225 Highly flammable liquid and vapour.

H312+H332 Harmful in contact with skin or if inhaled.

H315 Causes skin irritation.

H318 Causes serious eye damage.

Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

Results of PBT and vPvB assessment

PBT:Not applicable.

vPvB:Not applicable.

3- COMPOSITION/INFORMATION ON INGREDIENTS

Chemical characterization: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 108-94-1 EINECS: 203-631-1 Reg.nr.: 01-2119453616-35	cyclohexanone Xn R20/21/22; Xi R38-41 R10	25-50%
	Flam. Liq. 3, H226; Eye Dam. 1, H318; Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	
CAS: 108-65-6 EINECS: 203-603-9 Reg.nr.: 01-2119475791-29	2-methoxy-1-methylethyl acetate R10	25-50%
	Flam. Liq. 3, H226	
CAS: 112-07-2 EINECS: 203-933-3 Reg.nr.: 01-2119475112-47	2-butoxyethyl acetate Xn R20/21/22	≤ 10%
	Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49	acetone Xi R36; F R11 R66-67	≤ 10%
	Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336	

Additional information: For the wording of the listed risk phrases refer to section 16.

4- FIRST - AID MEASURE

Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

After inhalation: Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Call for a doctor immediately.

Most important symptoms and effects, both acute and delayed: No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.



5- FIRE - FIGHTING MEASURE

Extinguishing media

Suitable extinguishing agents: CO₂, sand, extinguishing powder. Do not use water.

For safety reasons unsuitable extinguishing agents: Water with full jet.

Special hazards arising from the substance or mixture

No further relevant information available.

Advice for firefighters

Protective equipment: Mouth respiratory protective device.

6- ACCIDENTAL RELEASE MEASURE

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7- HANDLING AND STORAGE

Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class: 3

Specific end use(s) No further relevant information available

8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Additional information about design of technical facilities: No further data; see item 7.

Control parameters

Ingredients with limit values that require monitoring at the workplace:	
108-94-1 cyclohexanone	
WEL	Short-term value: 82 mg/m ³ , 20 ppm Long-term value: 41 mg/m ³ , 10 ppm Sk, BMGV
108-65-6 2-methoxy-1-methylethyl acetate	
WEL	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
112-07-2 2-butoxyethyl acetate	
WEL	Short-term value: 332 mg/m ³ , 50 ppm Long-term value: 133 mg/m ³ , 20 ppm Sk
67-64-1 acetone	
WEL	Short-term value: 3620 mg/m ³ , 1500 ppm Long-term value: 1210 mg/m ³ , 500 ppm

Ingredients with biological limit values:	
108-94-1 cyclohexanone	
BMGV	2 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: cyclohexanol

Additional information: The lists valid during the making were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Respiratory protection: In case of brief exposure or low pollution use respiratory filter device.

In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands: Protective gloves (EN 374).

Material of gloves:

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.7 mm

Penetration time of glove material: Value for the permeation: Level ≤ 6 .
Eye protection: Tightly sealed goggles.

9 – PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties	
General Information	
Appearance:	
Form:	<i>Fluid</i>
Colour:	<i>According to product specification</i>
Odour:	<i>Characteristic</i>
Odour threshold:	<i>Not determined.</i>
pH-value:	<i>Not determined.</i>
Change in condition	
Melting point/Melting range:	<i>Undetermined.</i>
Boiling point/Boiling range:	<i>56 °C</i>
Flash point:	<i>9 °C (DIN 53213)</i>
Flammability (solid, gaseous):	<i>Not applicable.</i>
Ignition temperature:	<i>280 °C (DIN 51794)</i>
Decomposition temperature:	<i>Not determined.</i>
Self-igniting:	<i>Product is not selfigniting.</i>
Danger of explosion:	<i>Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.</i>
Explosion limits:	
Lower:	<i>1.3 Vol %</i>
Upper:	<i>13.0 Vol %</i>
Vapour pressure at 20 °C:	<i>233 hPa</i>
Density at 20 °C:	<i>0.935 g/cm³ (DIN 53217)</i>
Relative density	<i>Not determined.</i>
Vapour density	<i>Not determined.</i>
Evaporation rate	<i>Not determined.</i>
Solubility in / Miscibility with water:	<i>Not miscible or difficult to mix.</i>
Partition coefficient (n-octanol/ water):	<i>Not determined.</i>
Viscosity:	
Dynamic:	<i>Not determined.</i>
Kinematic at 20 °C:	<i>15 s (DIN 53211/4).</i>
Solvent content:	
VOC (EC)	<i>99.84 %</i>

Solids content (weight-%):	0.2 %
Other information	<i>No further relevant information available.</i>

10- STABILITY AND REACTIVITY

Reactivity No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions: No dangerous reactions known.

Conditions to avoid: No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: Carbon monoxide.

11- TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity:

Harmful in contact with skin or if inhaled.

LD/LC50 values relevant for classification:

108-94-1 cyclohexanone

Oral	LD50	1620 mg/kg (rat)
------	------	------------------

Primary irritant effect:

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitization Based on available data, the classification criteria are not met.

CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity Based on available data, the classification criteria are not met.

Carcinogenicity Based on available data, the classification criteria are not met.

Reproductive toxicity Based on available data, the classification criteria are not met.

STOT-single exposure Based on available data, the classification criteria are not met.

STOT-repeated exposure Based on available data, the classification criteria are not met.

Aspiration hazard Based on available data, the classification criteria are not met.

12 – ECOLOGICAL INFORMATION

Toxicity

Aquatic toxicity: No further relevant information available.

Persistence and degradability No further relevant information available.

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects No further relevant information available.

13– DISPOSAL CONSIDERATION

Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European	waste catalogue
14 06 03*	other solvents and solvent mixtures

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

14– TRANSPORT INFORMATION

UN-Number

ADR, IMDG, IATA

UN1263

UN proper shipping name

ADR

1263 PAINT RELATED MATERIAL, special provision 640D

IMDG, IATA

PAINT RELATED MATERIAL

Transport hazard class(es)

ADR



Class 3 (F1) Flammable liquids.
Label 3

IMDG, IATA



Class 3 Flammable liquids
Label 3

Packing group

ADR, IMDG, IATA II

Environmental hazards:

Marine pollutant: No

Special precautions for user

Danger code (Kemler): Warning: Flammable liquids.
33
EMS Number: F-E,S-E

Transport in bulk according to Annex II of

MARPOL and the IBC Code Not applicable.

Transport/Additional information:

ADR
Transport category 2
Tunnel restriction code D/E

IMDG
Limited quantities (LQ) 5L

UN "Model Regulation":

UN 1263 PAINT RELATED MATERIAL, SPECIAL PROVISION 640D, 3, II, (D/E)

15 – REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixt.

Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

National regulations:

Class	Share in %
NK	50-100

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16-OTHER INFORMATION

Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H336 May cause drowsiness or dizziness.

R10 Flammable.

R11 Highly flammable.

R20/21/22 Harmful by inhalation, in contact with skin and if swallowed.

R36 Irritating to eyes.

R38 Irritating to skin.

R41 Risk of serious damage to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

The information contained in these sheets is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.