

SAFETY DATA SHEET
according to 1907/2006/EC, Article 31

1- IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product details

Trade name: Aerosol Spot blender

Article number: 26504

Intended use: Car refinishing Product/ Preparation

Manufacturer/Supplier: Chamäleon GmbH

Rudolf-Diesel-Straße, 8a, 69155 Heidelberg -- Germany

Further information obtainable from: Product Safety Department

Information in case of emergency: + 49 70024112112 (CH)

2 – HAZARDS IDENTIFICATION

Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



GHS07

STOT SE 3 H336 May cause drowsiness or dizziness.

Classification according to Directive 67/548/EEC or Directive 1999/45/EC

F+; Extremely flammable

R12: Extremely flammable.

R66-67: Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent.

Warning! Pressurised container.

Has a narcotising effect.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02

GHS07

Signal word: Danger

Hazard-determining components of labelling:

n-butyl acetate

ethyl acetate

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P102 Keep out of reach of children.

P260 Do not breathe spray.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P251 Pressurized container: Do not pierce or burn, even after use.

P211 Do not spray on an open flame or other ignition source.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking

Other hazards

Results of PBT and vPvB assessment

PBT:Not applicable.

vPvB:Not applicable.

3- COMPOSITION/INFORMATION ON INGREDIENTS

Chemical characterization: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:		
CAS: 115-10-6 EINECS: 204-065-8 Index number: 603-019-00-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether F+ R12	50-75%
	Flam. Gas 1, H220; Flam. Liq. 1, H224 Press. Gas C, H280	
CAS: 123-86-4 EINECS: 204-658-1 Index number: 607-025-00-1 Reg.nr.: 01-2119485493-29-xxxx	n-butyl acetate R10-66-67	20-25%
	Flam. Liq. 3, H226 STOT SE 3, H336	
CAS: 141-78-6 EINECS: 205-500-4 Index number: 607-022-00-5 Reg.nr.: 01-2119475103-46-xxxx	ethyl acetate Xi R36 F R11 R66-67	5-10%
	Flam. Liq. 2, H225 Eye Irrit. 2, H319; STOT SE 3, H336	
CAS: 108-65-6 EINECS: 203-603-9 Index number: 607-195-00-7 Reg.nr.: 01-2119475791-29-xxxx	2-methoxy-1-methylethyl acetate R10	5-10%
	Flam. Liq. 3, H226	
CAS: 1330-20-7 EINECS: 215-535-7 Index number: 601-022-00-9 Reg.nr.: 01-2119488216-32-xxxx	xylene Xn R20/21 Xi R38 R10	2.5-5%
	Flam. Liq. 3, H226 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315	

Additional information: For the wording of the listed risk phrases refer to section 16.

4- FIRST - AID MEASURE

Description of first aid measures

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Generally the product does not irritate the skin.

After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

After swallowing: Drink plenty of water and provide fresh air. Call for a doctor immediately.

Most important symptoms and effects, both acute and delayed

No further relevant information available.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.



5- FIRE - FIGHTING MEASURE

Extinguishing media

Suitable extinguishing agents: CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet.

Special hazards arising from the substance or mixture

No further relevant information available.

Advice for firefighters

Protective equipment: No special measures required.

6- ACCIDENTAL RELEASE MEASURE

Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation

Keep away from ignition sources.

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up: Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7- HANDLING AND STORAGE

Precautions for safe handling: Ensure good ventilation/exhaustion at the workplace.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

Information about storage in one common storage facility: Not required

Further information about storage conditions: Protect from heat and direct sunlight.

Specific end use(s): No further relevant information available.

8 – EXPOSURE CONTROLS / PERSONAL PROTECTION

Additional information about design of technical facilities: No further data; see item 7.

Control parameters

Ingredients with limit values that require monitoring at the workplace:	
115-10-6 dimethyl ether	
WEL	Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm
123-86-4 n-butyl acetate	
WEL	Short-term value: 966 mg/m ³ , 200 ppm Long-term value: 724 mg/m ³ , 150 ppm
141-78-6 ethyl acetate	
WEL	Short-term value: 400 ppm Long-term value: 200 ppm
108-65-6 2-methoxy-1-methylethyl acetate	
WEL	Short-term value: 548 mg/m ³ , 100 ppm Long-term value: 274 mg/m ³ , 50 ppm Sk
1330-20-7 xylene	
WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV

Ingredients with biological limit values:	
1330-20-7 xylene	
BMGV	650 mmol/mol creatinine Medium: urine Sampling time: post shift Parameter: methyl hippuric acid

Additional information: The lists valid during the making were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Respiratory protection: Not required.

Protection of hands: Not required.

Material of gloves: Not required.

Penetration time of glove material: Not required.

Eye protection: Not required.

9 – PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties	
General Information	
Appearance:	
Form:	<i>Aerosol</i>
Colour:	<i>According to product specification</i>
Odour:	<i>Characteristic</i>
Odour threshold:	<i>Not determined.</i>
pH-value:	<i>Not determined.</i>
Change in condition	
Melting point/Melting range:	<i>Undetermined.</i>
Boiling point/Boiling range:	<i>Not applicable, as aerosol</i>
Flash point:	<i>< 0 °C (< 32 °F) Not applicable, as aerosol.</i>
Flammability (solid, gaseous):	<i>Not applicable.</i>
Ignition temperature:	<i>240 °C (464 °F)</i>
Decomposition temperature:	<i>Not determined.</i>
Self-igniting:	<i>Product is not selfigniting.</i>
Danger of explosion:	<i>Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.</i>
Explosion limits:	
Lower:	<i>1.2 Vol %</i>
Upper:	<i>26.2 Vol %</i>
Vapour pressure at 20 °C (68 °F):	<i>4000 hPa (3000 mm Hg)</i>
Density at 20 °C (68 °F):	<i>0.735 g/cm³ (6.134 lbs/gal)</i>
Relative density	<i>Not determined.</i>
Vapour density	<i>Not determined.</i>
Evaporation rate	<i>Not applicable.</i>
Solubility in / Miscibility with water:	<i>Not miscible or difficult to mix.</i>
Partition coefficient (n-octanol/ water):	<i>Not determined.</i>
Viscosity:	
Dynamic:	<i>Not determined.</i>
Kinematic:	<i>Not determined.</i>
Solvent content:	
Organic solvents:	<i>99.3 %</i>
EU-VOC:	<i>730.2 g/l</i>
EU-VOC in %:	<i>99.34 %</i>
Solids content:	<i>0.6 %</i>
Other information	<i>No further relevant information available.</i>

10- STABILITY AND REACTIVITY

Reactivity

Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

Possibility of hazardous reactions: No dangerous reactions known.

Conditions to avoid: No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: No dangerous decomposition products known.

11- TOXICOLOGICAL INFORMATION

Information on toxicological effects

Acute toxicity:

LD/LC50 values relevant for classification:		
115-10-6 dimethyl ether		
Inhalative	LC50/4 h	308 mg/m ³ (rat)
123-86-4 n-butyl acetate		
Oral	LD50	10770 mg/kg (rat)
Dermal	LD50	>17600 mg/kg (rabbit)
Inhalative	LC50/4 h	>21.0 mg/m ³ (rat)
141-78-6 ethyl acetate		
Oral	LD50	5620 mg/kg (rabbit)
Dermal	LD50	>18000 mg/kg (rabbit)
Inhalative	LC50/4 h	1600 mg/m ³ (rat)
108-65-6 2-methoxy-1-methylethyl acetate		
Oral	LD50	8532 mg/kg (rat)
Dermal	LD50	>5000 mg/kg (rabbit)
Inhalative	LC50/4 h	35.7 mg/m ³ (rat)
1330-20-7 xylene		
Oral	LD50	4300 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rabbit)
Inhalative	LC50/4 h	22.1 mg/m ³ (rat)

Primary irritant effect:

on the skin: No irritant effect.

on the eye: No irritating effect.

Sensitization: No sensitising effects known.

12 – ECOLOGICAL INFORMATION

Toxicity

Aquatic toxicity:	
115-10-6 dimethyl ether	
EC50 / 48 h	>4000 mg/l (daphnia magna)
123-86-4 n-butyl acetate	
EC50 / 48 h	44 mg/l (daphnia magna)
EC50 / 96 h	320 mg/l (algae)
LC50 / 24 h	205 mg/l (daphnia magna)
LC50 / 96 h	18 mg/l (Pimephales promelas)
141-78-6 ethyl acetate	
EC50 / 24 h	2500 mg/l (daphnia magna)
108-65-6 2-methoxy-1-methylethyl acetate	
EC50	408 mg/l (daphnia magna)
1330-20-7 xylene	
EC50 / 48 h	7.4 mg/l (daphnia magna)
LC50 / 96 h	13.5 mg/l (fish)

Persistence and degradability No further relevant information available.

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water.

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects No further relevant information available.

13– DISPOSAL CONSIDERATION

Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

European	waste catalogue
20 01 13*	solvents
15 01 04	metallic packaging



Uncleaned packaging:

Recommendation: Non contaminated packagings may be recycled

14- TRANSPORT INFORMATION

UN-Number

ADR, IMDG, IATA

UN 1950

UN proper shipping name

ADR

1950 AEROSOLS

IMDG

AEROSOLS

IATA

AEROSOLS, flammable

Transport hazard class(es)

ADR



Class

2 5F Gases.

Label

2.1

IMDG, IATA



Class

2.1

Label

2.1

Packing group

ADR, IMDG, IATA

Void

Environmental hazards:

Marine pollutant:

No

Special precautions for user

Warning: Gases.

Danger code (Kemler):

-

EMS Number:

F-D,S-U

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

Transport/Additional information:**ADR**

Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
Transport category	2
Tunnel restriction code	D

IMDG

Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity

UN "Model Regulation": UN1950, AEROSOLS, 2.1

15 – REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture: No further relevant information available.

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16-OTHER INFORMATION**Relevant phrases**

H220 Extremely flammable gas.
H224 Extremely flammable liquid and vapour.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H312 Harmful in contact with skin.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H336 May cause drowsiness or dizziness.

R10 Flammable.
R11 Highly flammable.
R12 Extremely flammable.
R20/21 Harmful by inhalation and in contact with skin.
R36 Irritating to eyes.
R38 Irritating to skin.
R66 Repeated exposure may cause skin dryness or cracking.



CHAMÁLEON GMBH / RUDOLF-DIESEL-STRASSE 8A / 69115 HEIDELBERG / GERMANY

CHAMÁLEON GMBH
RUDOLF-DIESEL-STRASSE 8A
69115 HEIDELBERG
GERMANY

FON 0049 (0) 6221 - 520 440
FAX 0049 (0) 6221 - 520 449
MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

R67 Vapours may cause drowsiness and dizziness.

The information contained in these sheets is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.