

FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449

MAIL INFO@CHAMAELEON-PRODUKTION.DE WEB WWW.CHAMAELEON-PRODUKTION.DE

SAFETY DATA SHEET according to 1907/2006/EC, Article 31 Revision date: 07.09.2021

1- IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

Product details

Trade name: 1K Primer fast **Article number:** 14225, 14227

Relevant identified uses of the substance or mixture and uses advised against:

No further relevant information available. **Intended use:** Car refinishing product/ Priming

Manufacturer/Supplier:

Chamäleon GmbH

Rudolf-Diesel-Straße, 8a, 69115 Heidelberg

Germany

Further information obtainable from: Product Safety Department **Information in case of emergency:** + 49 70024112112 (CH)

2 – HAZARDS IDENTIFICATION

Classification of the substance or mixture Classification according to Regulation (EC) No 1272/2008



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Eye Irrit. 2 H319 Causes serious eye irritation. Skin Sens. 1 H317 May cause an allergic skin reaction. STOT SE 3 H336 May cause drowsiness or dizziness.

Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.



GERMANY

FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449

MAIL INFO@CHAMAELEON-PRODUKTION.DE WEB WWW.CHAMAELEON-PRODUKTION.DE

Hazard pictograms





GHS02 GHS07

Signal word Danger

Hazard-determining components of labelling:

ethyl acetate

n-Butyl acetate

Hydrocarbons, C9, aromatics

butan-1-ol

Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H317 May cause an allergic skin reaction.

H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read carefully and follow all instructions.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

3– COMPOSITION/INFORMATION ON INGREDIENTS

Chemical characterization: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.



FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449

MAIL INFO@CHAMAELEON-PRODUKTION.DE WEB WWW.CHAMAELEON-PRODUKTION.DE

Dangerous components: 10-25% CAS: 141-78-6 ethyl acetate EINECS: 205-500-4 Reg.nr.: 01-2119475103-46 Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336 ≤20% CAS: 123-86-4 n-Butyl acetate EINECS: 204-658-1 Flam. Liq. 3, H226; STOT SE 3, H336 Reg.nr.: 01-2119485493-29 Nitrocellulose, nitrogen content <12,6% 2.5-<10% CAS: 9004-70-0 Expl. 1.1, H201 2.5-<5% Xylene CAS: 1330-20-7 Flam. Liq. 3, H226; STOT RE 2, H373; Asp. Tox. 1, EINECS: 215-535-7 H304; Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Reg.nr.: 01-2119488216-32 Irrit. 2, H315; Eye Irrit. 2, H319; STOT SE 3, H335 1-<2.5% Hydrocarbons, C9, aromatics CAS: 64742-95-6 EC number: 918-668-5 Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic Reg.nr.: 01-2119455851-35 2, H411; STOT SE 3, H335-H336 >1-<2.5% butan-1-ol CAS: 71-36-3 EINECS: 200-751-6 Flam. Liq. 3, H226; Eye Dam. 1, H318; Acute Tox. 4, Reg.nr.: 01-2119484630-38 H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336 >0.1-<1% Fatty acids, C18-unsatd., dimers, reaction products with CAS: 162627-17-0 N,Ndimethyl-1,3-propanediamine and1,3-propanediamine EC number: 605-296-0 Reg.nr.: 01-2119970640-38 Skin Sens. 1A, H317 <1%

Additional information: For the wording of the listed risk phrases refer to section 16.

Repr. 2, H361fd

1,1,1-Trimethylolpropane

<u>4– FIRST - AID MEASURE</u>

Description of first aid measures

General information: Immediately remove any clothing soiled by the product.

After inhalation:

CAS: 77-99-6

EINECS: 201-074-9

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

After skin contact:



FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449

MAIL INFO@CHAMAELEON-PRODUKTION.DE WEB WWW.CHAMAELEON-PRODUKTION.DE

Generally the product does not irritate the skin.

Immediately rinse with water.

After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

After swallowing: If symptoms persist consult doctor.

Indication of any immediate medical attention and special treatment needed

No further relevant information available.

<u>5– FIRE - FIGHTING MEASURE</u>

Extinguishing media

Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

For safety reasons unsuitable extinguishing agents: Water with full jet

Special hazards arising from the substance or mixture: No further relevant information available.

Advice for firefighters

Protective equipment: No special measures required.

6– ACCIDENTAL RELEASE MEASURE

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions: Do not allow to enter sewers/ surface or ground water.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7- HANDLING AND STORAGE

Precautions for safe handling

Keep away from heat and direct sunlight.

Ensure good ventilation/exhaustion at the workplace.



FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449

MAIL INFO@CHAMAELEON-PRODUKTION.DE WEB WWW.CHAMAELEON-PRODUKTION.DE

Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Conditions for safe storage, including any incompatibilities

Storage:

Requirements to be met by storerooms and receptacles: Store in a cool location.

Information about storage in one common storage facility: Store away from foodstuffs.

Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Storage class: 3

Specific end use(s) No further relevant information available.

8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Additional information about design of technical facilities: No further data; see item 7.

| Ingredients with limit values that require monitoring at the workplace: 141-78-6 ethyl acetate | | | | |
|---|--|--|--|--|
| | | | | |
| 123-86-4 | n-Butyl acetate | | | |
| WEL | Short-term value: 966 mg/m³, 200 ppm Long-term value: 724 mg/m³, 150 ppm | | | |
| 1330-20- | 7 Xylene | | | |
| WEL | Short-term value: 441 mg/m³, 100 ppm Long-term value: 220 mg/m³, 50 ppm Sk; BMGV | | | |
| 71-36-3 | butan-1-ol | | | |
| WEL | Short-term value: 154 mg/m³, 50 ppm Sk | | | |

| Ingredients with biological limit values: | |
|---|--|
| 1330-20-7 Xylene | |



FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449

MAIL INFO@CHAMAELEON-PRODUKTION.DE WEB WWW.CHAMAELEON-PRODUKTION.DE

650 mmol/mol creatinine

BMGV

Medium: urine

Sampling time: post shift

Parameter: methyl hippuric acid

Additional information: The lists valid during the making were used as basis.

Exposure controls

Personal protective equipment:

General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protection of hands:

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Eve protection:

Tightly sealed goggles

9 – PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

General Information

Appearance:

Form: Fluid

Colour: According to product specification

Odour:CharacteristicOdour threshold:Not determined.

pH-value: Not determined.

6



FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449

MAIL INFO@CHAMAELEON-PRODUKTION.DE WEB WWW.CHAMAELEON-PRODUKTION.DE

| Change in condition | |
|--|---|
| Melting point/freezing point: | Undetermined. |
| Initial boiling point and boiling range: | 77-78 °C |
| Flash point: | -4 °C (DIN EN ISO 1523:2002) |
| Flammability (solid, gas): | Not applicable. |
| Ignition temperature: | 370 °C (DIN 51794) |
| Decomposition temperature: | Not determined. |
| Auto-ignition temperature: | Product is not selfigniting. |
| Explosive properties: | Product is not explosive. However, formation of explosive air/vapour mixtures are possible. |
| Explosion limits: | |
| Lower: | 1.2 Vol % |
| Upper: | 11.5 Vol % |
| Vapour pressure at 20 °C: | 97 hPa |
| Density at 20 °C: | 1.384 g/cm³ (DIN EN ISO 2811-1) |
| Relative density | Not determined. |
| Vapour density | Not determined. |
| Evaporation rate | Not determined. |
| Solubility in / Miscibility with water: | Not miscible or difficult to mix. |
| Partition coefficient: n-octanol/water: | Not determined. |
| Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic at 20 °C: | 350-390 s (DIN 53211/4) |
| Solvent content: | |
| VOC (EC) | 40.37 % |
| Solids content (weight-%): | 59.6 % |
| Other information | No further relevant information available. |

<u>10– STABILITY AND REACTIVITY</u>

Reactivity No further relevant information available.

Chemical stability

Thermal decomposition / conditions to be avoided: No decomposition if used according to

Possibility of hazardous reactions: No dangerous reactions known. Conditions to avoid: No further relevant information available. **Incompatible materials:** No further relevant information available.



FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449

MAIL INFO@CHAMAELEON-PRODUKTION.DE

WEB WWW.CHAMAELEON-PRODUKTION.DE

Hazardous decomposition products: Carbon monoxide

11- TOXILOGICAL INFORMATION

Information on toxicological effects

Acute toxicity: Based on available data, the classification criteria are not met.

| LD/LC50 values relevant for classification: | | | | |
|---|--------------|---|--|--|
| 64742-95-6 Hydrocarbons, C9, aromatics | | | | |
| Oral Dermal | LD50 LD50 | >2,000 mg/kg (rat) >2,000 mg/kg (rabbit) | | |

Primary irritant effect:

Skin corrosion/irritation: Based on available data, the classification criteria are not met

Serious eye damage/irritation: Causes serious eye irritation.

Respiratory or skin sensitization:

May cause an allergic skin reaction.

Additional toxicological information:

CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Germ cell mutagenicity: Based on available data, the classification criteria are not met.

Carcinogenicity: Based on available data, the classification criteria are not met.

Reproductive toxicity: Based on available data, the classification criteria are not met.

STOT-single exposure:

May cause drowsiness or dizziness.

STOT-repeated exposure: Based on available data, the classification criteria are not met.

Aspiration hazard: Based on available data, the classification criteria are not met.

<u>12 – ECOLOGICAL INFORMATION</u>

Toxicity

Aquatic toxicity: No further relevant information available.

Persistence and degradability No further relevant information available.

Bioaccumulative potential No further relevant information available.

Mobility in soil No further relevant information available.

Additional ecological information:

Water hazard class 1 (German Regulation): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

8



FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449

MAIL INFO@CHAMAELEON-PRODUKTION.DE WEB WWW.CHAMAELEON-PRODUKTION.DE

Results of PBT and vPvB assessment

PBT: Not applicable. vPvB: Not applicable.

Other adverse effects No further relevant information available.

13-DISPOSAL CONSIDERATION

Waste treatment methods

Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Uncleaned packaging:

Recommendation: Disposal must be made according to official regulations.

14– TRANSPORT INFORMATION

UN-Number

ADR, IMDG, IATA UN1263

UN proper shipping name

ADR UN1263 PAINT

IMDG, IATA **PAINT**

Transport hazard class(es) ADR



Class 3 (F1) Flammable liquids Label

IMDG, IATA



Chamäleon GmbH- Safety Data Sheet



FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449

MAIL INFO@CHAMAELEON-PRODUKTION.DE WEB WWW.CHAMAELEON-PRODUKTION.DE

Class 3 Flammable liquids

Label

Packing group

ADR, IMDG, IATA II

Environmental hazards:

Marine pollutant: No

Special precautions for user Warning: Flammable liquids

Hazard identification number (Kemler code): 33 **EMS Number:** F-E,<u>S-E</u>

Stowage Category В

Transport in bulk according to Annex II of

Marpol and the IBC Code Not applicable.

Transport/Additional information:

ADR

Limited quantities (LQ) 5L **Transport category** 2 **Tunnel restriction code** D/E

IMDG

Limited quantities (LQ) 5L

UN "Model Regulation": UN 1263 PAINT, 3, II

<u> 15 – REGULATORY INFORMATION</u>

Safety, health and environmental regulations/legislation specific for the substance or mixture Directive 2012/18/EU

Named dangerous substances - ANNEX I None of the ingredients is listed.

Seveso category P5c FLAMMABLE LIQUIDS

Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t **National regulations:**

Additional classification according to Decree on Hazardous Materials, Annex II:

Class Share in %



FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449

MAIL INFO@CHAMAELEON-PRODUKTION.DE WEB WWW.CHAMAELEON-PRODUKTION.DE

NK 25-50

Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

<u>16-OTHER INFORMATION</u>

Relevant phrases

H201 Explosive; mass explosion hazard.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H361fd Suspected of damaging fertility. Suspected of damaging the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Classification according to Regulation (EC) No 1272/2008

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Expl. 1.1: Explosives – Division 1.1

Flam. Liq. 2: Flammable liquids – Category 2



GERMANY

FON 0049 (0) 6221 - 520 440 FAX 0049 (0) 6221 - 520 449

MAIL INFO@CHAMAELEON-PRODUKTION.DE WEB WWW.CHAMAELEON-PRODUKTION.DE

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 4: Acute toxicity – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Skin Sens. 1: Skin sensitisation – Category 1

Skin Sens. 1A: Skin sensitisation – Category 1A

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

The information contained in these sheets is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.