

***SAFETY DATA SHEET***  
***according to 1907/2006/EC, Article 31***

*Revision date: 21.08.2023*

**1- IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/  
UNDERTAKING**

**Product details**

**Trade name:** Hardener for 499 Express primer

**Article number:** 12993

**Relevant identified uses of the substance or mixture and uses advised against:**

No further relevant information available.

**Intended use:** Car refinishing product/ Hardening agent/ Curing agent

**Manufacturer/Supplier:**

Chamäleon GmbH

Rudolf-Diesel-Straße, 8a, 69115 Heidelberg

Germany

**Further information obtainable from:** Product Safety Department

**Information in case of emergency:** + 49 70024112112 (CH)

**2 – HAZARDS IDENTIFICATION**

**Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008**



flame

Flam. Liq. 3 H226

Flammable liquid and vapour.



Acute Tox. 4 H332 Harmful if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

**Label elements**

**Labelling according to Regulation (EC) No 1272/2008**

The product is classified and labelled according to the GB CLP regulation.

## Hazard pictograms



GHS02 GHS07

**Signal word** Warning**Hazard-determining components of labelling:**

Hexamethylene diisocyanate, oligomers

n-Butyl acetate

2-Ethoxy-1-methylethyl acetate

hexamethylene-di-isocyanate

**Hazard statements**

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H317 May cause an allergic skin reaction.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

**Precautionary statements**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P312 Call a POISON CENTER/doctor if you feel unwell.

**Additional information:**

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH204 Contains isocyanates. May produce an allergic reaction.

Restricted to professional users.

**Other hazards****Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

## 3- COMPOSITION/INFORMATION ON INGREDIENTS

**Mixtures****Description:** Mixture of substances listed below with nonhazardous additions.**Dangerous components:**

CAS: 28182-81-2 NLP: 500-060-2 Reg.nr.: 01-2119485796-17	Hexamethylene diisocyanate, oligomers	50-100%
	Acute Tox. 4, H332; Skin Sens. 1, H317; STOT SE 3, H335, EUH204	
CAS: 123-86-4 EINECS: 204-658-1 Reg.nr.: 01-2119485493-29	n-Butyl acetate	25-50%
	Flam. Liq. 3, H226; STOT SE 3, H336, EUH066	
CAS: 54839-24-6 EINECS: 259-370-9 Reg.nr.: 01-2119475116-39	2-Ethoxy-1-methylethyl acetate	10-25%
	Flam. Liq. 3, H226; STOT SE 3, H336	
CAS: 77-58-7 EINECS: 201-039-8 Reg.nr.: 01-2119496068-27	dibutyltin dilaurate	≥0.1-<0.25%
	Muta. 2, H341; Repr. 1B, H360FD; STOT SE 1, H370; STOT RE 1, H372; Skin Corr. 1C, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Skin Sens. 1, H317	
CAS: 822-06-0 EINECS: 212-485-8 Reg.nr.: 01-2119457571-37	hexamethylene-di-isocyanate	<0.1%
	Acute Tox. 2, H330; Resp. Sens. 1, H334; Acute Tox. 4, H302; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335, EUH204 Specific concentration limits: Resp. Sens. 1; H334: C ≥ 0.5 % Skin Sens. 1; H317: C ≥ 0.5 %	

**Additional information:** For the wording of the listed hazard phrases refer to section 16.

#### **4- FIRST - AID MEASURE**

##### **Description of first aid measures**

###### **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

In case of irregular breathing or respiratory arrest provide artificial respiration.

###### **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:** Immediately rinse with water.

###### **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

**After swallowing:** If symptoms persist consult doctor.

**Most important symptoms and effects, both acute and delayed** No further relevant information

available.

**Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

**5- FIRE - FIGHTING MEASURE**

**Extinguishing media**

**Suitable extinguishing agents:**

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

**For safety reasons unsuitable extinguishing agents:** Water with full jet

**Special hazards arising from the substance or mixture:**

In case of fire, the following can be released:

Nitrogen oxides (NO<sub>x</sub>)

Carbon monoxide (CO)

Hydrogen cyanide (HCN)

**Advice for firefighters:**

**Protective equipment:** Mouth respiratory protective device.

**6- ACCIDENTAL RELEASE MEASURE**

**Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

**Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

**Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Contain and collect spillages with non-combustible absorbent materials (e.g. sand, earth, diatomaceous earth) and place in a suitable container.

Decontaminate immediately with suitable mixture (flammable):

- as such usable (inflammatory!):

water	45 Vol.%
ethanol or isopropanol	50 Vol.%
ammonia solution (Density= 0.88)	5 Vol.%
- alternatively (non-flammable):

sodium carbonate	5 Vol.%
water	95 Vol.%

Add the same decontaminant to any residues and allow to stand for several days in a non-sealed container until no further reaction occurs. Once this stage is reached, close the container and dispose of

in accordance with the waste regulations (see Section 13).

**Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**7- HANDLING AND STORAGE**

**Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

Persons with a history of asthma, allergies or chronic or recurrent respiratory diseases should only be employed in processes in which this product is used under appropriate medical supervision.

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

**Conditions for safe storage, including any incompatibilities**

**Storage:**

**Requirements to be met by storerooms and receptacles:** No special requirements.

**Information about storage in one common storage facility:**

Do not store together with reducing agents, heavy-metal compounds, acids and alkalis.

Store away from foodstuffs.

**Further information about storage conditions:**

Keep container tightly sealed.

Store separately from oxidising agents, strongly alkaline and strongly acidic materials, amines, alcohol and water.

**Storage class:** 3

**Specific end use(s)** No further relevant information available.

**8- EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Control parameters**

<b>Ingredients with limit values that require monitoring at the workplace:</b>	
28182-81-2 Hexamethylene diisocyanate, oligomers	
EBW	Short-term value: 0.5 mg/m <sup>3</sup> exposition evaluation valu TRGS 430 (EBW)
123-86-4 n-Butyl acetate	

WEL	Short-term value: 966 mg/m <sup>3</sup> , 200 ppm Long-term value: 724 mg/m <sup>3</sup> , 150 ppm
77-58-7 dibutyltin dilaurate	
WEL	Short-term value: 0.2 mg/m <sup>3</sup> Long-term value: 0.1 mg/m <sup>3</sup> as Sn; Sk
822-06-0 hexamethylene-di-isocyanate	
WEL	Short-term value: 0.07 mg/m <sup>3</sup> Long-term value: 0.02 mg/m <sup>3</sup> Sen; as -NCO
<b>Ingredients with biological limit values:</b>	
822-06-0 hexamethylene-di-isocyanate	
BMGV	1 µmol creatinine/mol Medium: urine Sampling time: At the end of the period od exposure Parameter: isocyanate-derived diamine

**Additional information:** The lists valid during the making were used as basis.

### Exposure controls

**Appropriate engineering controls** No further data; see section 7.

### Individual protection measures, such as personal protective equipment:

All personal protective equipment, including respiratory protective equipment, used to control exposure to hazardous substances must be selected to meet the requirements of the COSHH Regulations.

### General protective and hygienic measures:

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

### Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

### Hand protection:

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Protective gloves (EN 374)

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

**Eye protection:** Tightly sealed goggles

## 9- PHYSICAL AND CHEMICAL PROPERTIES

<b>Information on basic physical and chemical properties</b>	
<b>General Information</b>	
<b>Physical state:</b>	<i>Fluid</i>
<b>Colour:</b>	<i>According to product specification</i>
<b>Odour:</b>	<i>Characteristic</i>
<b>Odour threshold:</b>	<i>Not determined.</i>
<b>Melting point/freezing point:</b>	<i>Undetermined.</i>
<b>Boiling point or initial boiling point and boiling range</b>	<i>124-128 °C</i>
<b>Flammability</b>	<i>Flammable</i>
<b>Lower and upper explosion limit</b>	
<b>Lower:</b>	<i>1.2 Vol %</i>
<b>Upper:</b>	<i>7.5 Vol %</i>
<b>Flash point:</b>	<i>27 °C (DIN EN ISO 1523:2002)</i>
<b>Auto-ignition temperature:</b>	<i>370 °C (DIN 51794)</i>
<b>Decomposition temperature:</b>	<i>Not determined.</i>
<b>pH</b>	<i>Not determined.</i>
<b>Viscosity:</b>	
<b>Kinematic viscosity at 20 °C</b>	<i>10-15 s (DIN 53211/4)</i>
<b>Dynamic:</b>	<i>Not determined.</i>
<b>Solubility</b>	
<b>water:</b>	<i>Not miscible or difficult to mix.</i>
<b>Partition coefficient n-octanol/water (log value)</b>	<i>Not determined.</i>
<b>Vapour pressure at 20 °C:</b>	<i>10.7 hPa</i>
<b>Vapour pressure at 50 °C:</b>	<i>55 hPa</i>
<b>Density and/or relative density</b>	
<b>Density at 20 °C:</b>	<i>1.029 g/cm<sup>3</sup> (DIN EN ISO 2811-1)</i>
<b>Relative density</b>	<i>Not determined.</i>
<b>Vapour density</b>	<i>Not determined.</i>
<b>9.2 Other information</b>	
<b>Appearance:</b>	
<b>Form:</b>	<i>Fluid</i>
<b>Important information on protection of health and environment, and on safety.</b>	
<b>Ignition temperature:</b>	<i>Product is not selfigniting.</i>
<b>Explosive properties:</b>	<i>Product is not explosive. However, formation of explosive air/vapour mixtures are possible.</i>
<b>Solvent content:</b>	

<b>VOC (EC)</b>	45.54 %
<b>Solids content (weight-%):</b>	54.5 %
<b>Change in condition</b>	
<b>Evaporation rate</b>	<i>Not determined.</i>
<b>Information with regard to physical hazard classes</b>	
<b>Explosives</b>	<i>Void</i>
<b>Flammable gases</b>	<i>Void</i>
<b>Aerosols</b>	<i>Void</i>
<b>Oxidising gases</b>	<i>Void</i>
<b>Gases under pressure</b>	<i>Void</i>
<b>Flammable liquids</b>	<i>Flammable liquid and vapour.</i>
<b>Flammable solids</b>	<i>Void</i>
<b>Self-reactive substances and mixtures</b>	<i>Void</i>
<b>Pyrophoric liquids</b>	<i>Void</i>
<b>Pyrophoric solids</b>	<i>Void</i>
<b>Self-heating substances and mixtures</b>	<i>Void</i>
<b>Substances and mixtures, which emit flammable gases in contact with water</b>	<i>Void</i>
<b>Oxidising liquids</b>	<i>Void</i>
<b>Oxidising solids</b>	<i>Void</i>
<b>Organic peroxides</b>	<i>Void</i>
<b>Corrosive to metals</b>	<i>Void</i>
<b>Desensitised explosives</b>	<i>Void</i>

## 10- STABILITY AND REACTIVITY

**Reactivity:** No further relevant information available.

**Chemical stability**

**Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

**Possibility of hazardous reactions:** No dangerous reactions known.

**Conditions to avoid:** No further relevant information available.

**Incompatible materials:** No further relevant information available.

**Hazardous decomposition products:**

Possible in traces.

Nitrogen oxides

Hydrogen chloride (HCl)



Hydrogen cyanide (prussic acid)  
Carbon monoxide  
Nitrogen oxides (NO<sub>x</sub>)

## **11 – TOXICOLOGICAL INFORMATION**

**Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity:** Harmful if inhaled.

<b>LD/LC50 values relevant for classification:</b>		
28182-81-2 Hexamethylene diisocyanate, oligomers		
Inhalative	LC50/4 h	1.5 mg/l (rat)

**Respiratory or skin sensitisation** May cause an allergic skin reaction.

**STOT-single exposure** May cause respiratory irritation. May cause drowsiness or dizziness.

## **12 – ECOLOGICAL INFORMATION**

### **Toxicity**

**Aquatic toxicity:** No further relevant information available.

**Persistence and degradability:** No further relevant information available.

**Bioaccumulative potential:** No further relevant information available.

**Mobility in soil:** No further relevant information available.

### **Results of PBT and vPvB assessment:**

PBT: Not applicable.

vPvB: Not applicable.

### **Endocrine disrupting properties**

The product does not contain substances with endocrine disrupting properties.

### **Other adverse effects:**

### **Additional ecological information:**

#### **General notes:**

Water hazard class 1 (German Regulation): slightly hazardous for water. Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

## **13 – DISPOSAL CONSIDERATION**

### **Waste treatment methods**

#### **Recommendation:**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**Uncleaned packaging:**

**Recommendation:**

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

**14- TRANSPORT INFORMATION**

**UN-Number or ID-number**

ADR, IMDG, IATA UN1263

**UN proper shipping name**

ADR UN1263 PAINT RELATED MATERIAL  
IMDG, IATA PAINT RELATED MATERIAL

**Transport hazard class(es)**

**ADR**



Class 3 (F1) Flammable liquids.  
Label 3

**IMDG, IATA**



Class 3 Flammable liquids.  
Label 3

**Packing group**

ADR, IMDG, IATA III

**Environmental hazards:** Not applicable.

**Special precautions for user** Warning: Flammable liquids.

Hazard identification number (Kemler code): 30

EMS Number: F-E,S-E

Stowage Category A

**Maritime transport in bulk according to IMO instruments** Not applicable.

**Transport/Additional information:**

**ADR**

**Limited quantities (LQ)** 5L  
**Transport category** 3  
**Tunnel restriction code** D/E

**IMDG**

**Limited quantities (LQ)** 5L

**UN "Model Regulation":** UN 1263 PAINT RELATED MATERIAL, 3, III

**15 – REGULATORY INFORMATION**

**Safety, health and environmental regulations/legislation specific for the substance or mixture.**

**Directive 2012/18/EU**

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**Seveso category P5c** FLAMMABLE LIQUIDS

**Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t

**Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t

**National regulations:**

**Additional classification according to Decree on Hazardous Materials, Annex II:**

Class	Share in %
NK	25-50

**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

**16-OTHER INFORMATION**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Relevant phrases**

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H319 Causes serious eye irritation.
- H330 Fatal if inhaled.
- H332 Harmful if inhaled.
- H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H341 Suspected of causing genetic defects.
- H360FD May damage fertility. May damage the unborn child.
- H370 Causes damage to organs.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- EUH066 Repeated exposure may cause skin dryness or cracking.
- EUH204 Contains isocyanates. May produce an allergic reaction.

**Classification according to Regulation (EC) No 1272/2008**

The classification of the mixture is generally based on the calculation method using substance data according to Regulation (EC) No 1272/2008.

**Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route  
(European Agreement Concerning the  
International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 2: Acute toxicity – Category 2

Acute Tox. 4: Acute toxicity – Category 4

Skin Corr. 1C: Skin corrosion/irritation – Category 1C

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

- Muta. 2: Germ cell mutagenicity – Category 2
- Repr. 1B: Reproductive toxicity – Category 1B
- STOT SE 1: Specific target organ toxicity (single exposure) – Category 1
- STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
- STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1
- Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1
- Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1

The information contained in these sheets is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.