

TECHNICAL DATA SHEET

Revision date: 31.08.2023

BITUMEN BRASHABLE

- Article number:** 37111
- Color:** black
- Intended use:** Car refinishing product/Protective coatings
- General characteristics:**

Bitumen brushable is a highly resistant coating for floor pans, wheel houses and so on. It provides a durable protection against corrosion, de-icing salt and stone-chips.

 - Excellent adhesion
 - Shock- and scratch-resistant
 - Long-term flexible film
 - Good sound deadening properties
 - Non-drip application

Physical & chemical data:

- Hardener:** -
- Mixing ratio:** -
- Dilution:** Ready to use
- Spraying viscosity:** 4 mm DIN
- Content:** 1 kg
- Pot life at 20 °C:** -

Application process:

Before use, carefully read and observe the warning texts on the label!

Application method	Pressure	Nozzle
Brush or special UBS brush	--	--

Spraying operations	DFT	Consumption

--	approx. 3 mm	1 - 2 m ² /l
----	--------------	-------------------------

Flash-off time
--

Processing conditions:

Please only use in an adequate ventilated environment with an ample supply of fresh air. Processing temperature should be at least +10 °C and max. air humidity should not exceed 80%.

Processing tips:

The surface must be cleaned thoroughly. It must be dry, free from dust, grease, oil and rust. Old non-adherent underbody coating must be removed.

Do not apply on engine, transmission, sump, cardan shaft, exhaust pipes, axles, springs, shock absorber, brake cables, grease nipples, etc.

VOC regulation:

EU limit value: Category B/e 840 g/l

This product contains max. 840 g/l.

Storage stability: 36 months at 70°F (20°C) if stored in tightly closed original containers.

This release replaces all eventually earlier issued versions.

For additional information, not contained in this technical data sheet, please contact the supplier under:

e-mail: info@chamaeleon-produktion.de

For safety information, please refer to the corresponding safety data sheet.