



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: info@chamaeleon-produktion.de  
http: //www.chamaeleon-produktion.de

## TECHNICAL DATA SHEET

# BRUSHABLE SEALANT

**Article number:** 37640

**Intended use:** Car refinishing Product/ Sealant

**General characteristics:** Brushable sealant is a one-component brushable sealer used in car refinishing for the sealing of all bodywork joints, boots, wheel arches, etc.




**Product characteristics:**

- It has excellent sealing characteristics as well as being very resistant to torsion, water and vibrations. All of these characteristics remain unchanged for a lifetime.
- The low solvent content and the high quantity of resin used guarantees an excellent adhesion and a very high cohesion to any kind of supporting surface, and even with thick applications the paint will not break.
- Brushable sealant can be overpainted with any kind of paint.

### Physical and Chemical Characteristics:

Nature: Elastomers and synthetic resins  
Colour: Metallic grey  
Specific weight: 1,1 kg/l at 20°C  
VOC: 2004/42/EC - IIB(b)(250) <250g/l

### Applications:

		
		20' -30'

### Remarks:

Clean and degrease the part to be treated. Brush on with smooth continuous strokes, always in the same direction. Do not re-touch more than 3 minutes after application.  
It is recommended to overpaint approximately at 1 or 2 hours minimum if oven dried, to avoid solvent popping.



Chamäleon GmbH  
Rudolf-Diesel-Straße, 8a  
69115 Heidelberg-Germany  
Tel.: +49-(0)-6221 520440  
Fax: +49-(0)-6221 520449  
E-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)  
<http://www.chamaeleon-produktion.de>

**Equipment cleaning:**

Clean with a cleaning thinner.

**Safety:**

Follow instructions of product label. For more information check the Safety Data Sheet. Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

**Storage:**

Store the product in a ventilated place far from direct exposure to sunlight. Keep between +5°C and +30°C.

**Guarantee:**

In unopened original packaging, one year from manufacturing date.

*Data: 12, September 2015*

*This release replaces all eventually earlier issued versions.*

*For the additional information that is not included to the Technical Data Sheet apply to the supplier: e-mail: [info@chamaeleon-produktion.de](mailto:info@chamaeleon-produktion.de)*

*See information on safety in Safety Data Sheet.*