

TECHNICAL DATA SHEET

Revision date: 15.02.2024

MULTI-PURPOSE SPRAY

Article number:	27009
Color:	Transparent
Intended use:	Car refinishing product/Lubricant

General characteristics: Multi-purpose spray is a universal oil that lubricates, protects and cleans. Has a cleaning effect and removes oil, grease, wax and tar. It offers excellent penetration, is moisture-repellent, prevents rust, and leaves a protective film.

TECHNICAL CHARACTERISTICS

Base: Mineral oil with additives
Smell: Characteristic
Size: aerosol cans, maximum nominal volume 500 ml
Flash point: 62 °C
Relative density: 0.8 g/ml; 0.81 g/ml
Spray rate: 1,98
Vapour pressure: 3500/20 bar; 56/20 bar

Substrates:

Chains liable to light load, fastenings, locks, tools, garden tools, machinery, fasteners, pedals, home trainers, skaters, skates, skateboards

APPLICATION PROCESS

Processing conditions:

Please only use in an adequate ventilated environment with an ample supply of fresh air. Processing temperature should be at least +12 °C and max. air humidity should not exceed 80%.

Before use, carefully read and observe the warning texts on the label!

Processing tips:

- Before use, shake the aerosol.
- Apply multi spray in the desired quantity.
- The optimum lubrication is obtained after evaporation of the solvent.

The drying time depends on surrounding temperature, air humidity and thickness of the applied coat.

Shelf life:

120 months, if appropriate storage provided (=10°-25°C, relative air humidity of max. 60%)

This release replaces all eventually earlier issued versions.

For additional information, not contained in this technical data sheet, please contact the supplier under:

e-mail: info@chamaeleon-produktion.de

For safety information, please refer to the corresponding Safety data sheet.