

TECHNICAL DATA SHEET*Revision date: 24.08.2023***PRE-FILL PREMIUM**

Article number:	25005
Colour:	depending on filling
Intended use:	Car refinishing product/ Preparation
General characteristics:	<p>Chamäleon Pre-fill premium is a pre-filled can with propellant gases and solvent (275 ml) that can be filled with solvent-based basecoats (max. 100 ml). Ideal for spot repair or refinishing parts.</p> <p>A spray can pre-filled with propellant and solvents. The paint is transferred via a filling device into the can to produce a ready-to-use end product (dealers liability)</p> <ul style="list-style-type: none">▪ simple, time-saving application▪ excellent atomisation▪ light blending▪ professional adjustable nozzle

Physical characteristics:**Smell:** solvent**Efficiency:** depending on consistence and colour of the ground**Substrate:** depending on the colour of the substrate applicable on Primer filler, 2K Primer filler, 1K Epoxy primer, cured paint sanded**Drying time at 20°C, 50% relative air humidity:** drying time depends on surrounding temperature, air humidity, thickness of the applied coat and the filled type of paint (refer to information of the paint manufacturer)**Size:** aerosol cans, maximum nominal volume 400 ml.**VOC-value:** 218g**Processing conditions:**

Please only use in an adequate ventilated environment with an ample supply of fresh air. Processing temperature should be at least +10 °C and max. air humidity should not exceed 80%.

Application process:

Before use, carefully read and observe the warning texts on the label!

- Clean the surface to be painted thoroughly with Chamäleon Silicone remover, then sand
- Larger bare surfaces must be pre-primed with the appropriate Chamäleon primer
- The area must be dry and free of dust and grease
- Shake the can vigorously for 2 minutes
- Carry our spray test
- Compatibility testing is necessary

For professional use only

Wear an appropriate respirator (recommended type A2/P3).

Storage stability:

Empty cans: 5 years.

Filled cans: depending on type of paint from several hours up to 6 month (information from a specialist dealer). If appropriate storage provided (=10°-25°C, relative air humidity max. 60%)

This release replaces all eventually earlier issued versions.

For additional information, not contained in this technical data sheet, please contact the supplier under:

e-mail: info@chamaeleon-produktion.de

For safety information, please refer to the corresponding safety data sheet.