



CHAMĂI FON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG

FON 0049 (0) 6221 - 520 440

Revision date: 10.06.2023

FAX 0049 (0) 6221 - 520 449 MAIL INFO@CHAMAELEON-PRODUKTION.DE WEB WWW.CHAMAELEON-PRODUKTION.DE

TECHNICAL DATA SHEET

SOFT ABRASIVE ROLL

Article number: 47040, 47041, 47042, 47043, 47044, 47045,

47046, 47047, 47048, 47049

Colour: yellow

Intended use: Car refinishing product/ Grinding

General characteristics: This product with its soft, flexible characteristics, has

> been developed for hand sanding irregular and contoured surfaces and small, hard-to-reach parts.

These features make Soft roll pre cut particularly ideal for the automotive sector. The special stearate coating process prevents clogging and it is suitable for dry

sanding.

Available format: rolls

automotive **Productive sector:** marine

> wood composite

Technical details:

Baking: B-weight (P80-P180), A-weight (P240-P1000)

Coating: Open

Grain: Aluminium oxide

Stearate: Yes

Bonding: Double resin, antistatic

Grit: P150, P180, P220, P240, P320, P400, P500, P600, P800, P1000

Sizes: 115x25 m

Working processes:

Belt

Hand sanding





CHAMÄLEON GMBH RUDOLF-DIESEL-STRASSE 8A 69115 HEIDELBERG GERMANY

FON 0049 (0) 6221 - 520 440

FAX 0049 (0) 6221 - 520 449
MAIL INFO@CHAMAELEON-PRODUKTION.DE
WEB WWW.CHAMAELEON-PRODUKTION.DE

Available articles:

Grit:	P150	P180	P220	P240	P320
Article:	47040	47041	47042	47043	47044
Grit:	P400	P500	P600	P800	P1000
Article:	47045	47046	47047	47048	47049

This release replaces all eventually earlier issued versions.

For additional information, not contained in this Technical data sheet, please contact the supplier via: info@chamaeleon-produktion.de

For safety information, please refer to the corresponding Safety data sheet.