

TECHNICAL DATA SHEET*Revision date: 16.07.2024***1 K WASH PRIMER**

Article number:	26022, 26023
Colour:	red brown, olive
Intended use:	Car refinishing product/ Lacquer

General characteristics:

1 K Wash primer has excellent adhesive properties, especially on polished metal, e.g. steel plate. Active rust protection pigments ensure optimal corrosion protection. Can also be used as a welding primer. For best possible preparation of metal substrates, use Chamäleon Silicone remover for thorough precleaning. 2K Primer is recommended as an ideal secondary product. Ideal for spot repairs and refinishing parts.

- 1 K acid primer, welder primer
- Simple, time-saving application
- Fast drying time

TECHNICAL CHARACTERISTICS**Basis of binder:** NC**Smell:** solvent**Temperature resistance:** to 90 °C**Substrate:** sanded: blank metal, cured paintings, primer for refinishing parts, polyester substrates, aluminum, galvanized sheet metals with 3-layer structure.**Colour:** please note that the colour of the paint is not 100% identical to that of the cap**APPLICATION PROCESS**

Before use, carefully read and observe the warning texts on the label!

Processing conditions:

Please only use in an adequately ventilated environment with an ample supply of fresh air. Processing temperature should be at least +12 °C and max. air humidity should not exceed 80%.

Processing tips

- Remove all rust damaged area, clean surface thoroughly and sand.
- Area must be dry and free of grease and dust
- Clean undercoat with Chamäleon Silicone remover.
- Shake the can vigorously for 2 minutes.
- Carry out test spray.
- Apply 1-2 coats, when used as a primer.
- Apply one light coat when used as a welding primer.
- Air for 10-15 minutes (20° C), then recoat with 1K fillers or 2K hi-speed primer.

Spraying operations	DFT	Consumption
1-2 coats, when used as a primer	20 - 30 µm	1 m ²
1 light coat when used as a welding primer		

Drying	Dry to touch
Air drying 20 °C	10-15 min
IR drying	8-10 min

ATTENTION

- Please note that the colour of the paint is not 100% identical to that of the cap.
- We strongly recommend to test-spray before application.

VOC regulation:

EU limit value: Category B/e 840 g/l

This product contains max. 676.6 g/l VOC

Shelf life:

120 months, if stored in tightly closed original containers.

This release replaces all eventually earlier issued versions.

For additional information, not contained in this technical data sheet, please contact the supplier under:
e-mail: info@chamaeleon-produktion.de

For safety information, please refer to the corresponding safety data sheet.