

***SAFETY DATA SHEET***  
***according to 1907/2006/EC, Article 31***      *Revision date: 25.11.2015*

**1- IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING**

**Product details**

**Trade name:** 1K Acrylic paint SILVER RAL 9006

**Article number:** 50020

**Intended use:** Car refinishing Product/ Lacquer

**Manufacturer/Supplier:** Chamäleon GmbH

Rudolf-Diesel-Straße, 8a, 69115 Heidelberg -- Germany

**Further information obtainable from:** Product Safety Department

**Information in case of emergency:** + 49 70024112112 (CH)

**2 – HAZARDS IDENTIFICATION**

**Classification of the substance or mixture**

**Classification according to Regulation (EC) No 1272/2008**



GHS02 flame

Flam. Liq. 3    H226 Flammable liquid and vapour.



GHS07

Eye Irrit. 2    H319 Causes serious eye irritation.

STOT SE 3    H336 May cause drowsiness or dizziness.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

**Classification according to Directive 67/548/EEC or Directive 1999/45/EC**

R10-52/53-66-67: Flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

**Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

At long or repeated contact with skin it may cause dermatitis due to the degreasing effect of the solvent. Has a narcotizing effect.

### Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

### Label elements

#### Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

### Hazard pictograms



GHS02

GHS07

**Signal word:** Warning

### Hazard-determining components of labelling:

n-butyl acetate

Solvent naphtha (petroleum), light arom.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics

isobutanol

### Hazard statements:

H226 Flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

H412 Harmful to aquatic life with long lasting effects.

### Precautionary statements:

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### Additional information:

EUH066 Repeated exposure may cause skin dryness or cracking.

### Other hazards

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

### **3- COMPOSITION/INFORMATION ON INGREDIENTS**

#### **Chemical characterization: Mixtures**

**Description:** Mixture of substances listed below with nonhazardous additions.

|  |   |           |
|--|---|-----------|
| Dangerous components:  |   |           |
| CAS: 123-86-4<br>EINECS: 204-658-1<br>Reg.nr.:01-2119485493-29   | n-butyl acetate<br>R10-66-67  | 25-50%    |
|  | Flam. Liq. 3, H226; STOT SE 3, H336   |           |
| CAS: 64742-95-6<br>EINECS: 265-199-0                             | Solvent naphtha (petroleum), light arom.<br>Xn R65; Xi R37; N R51/53<br>R10-66-67           | 2.5-<10%  |
|  | Flam. Liq. 3, H226; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H335-H336        |           |
| EC number: 919-857-5<br>Reg.nr.: 01-2119463258-33                | Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, < 2% aromatics<br>Xn R65<br>R10-66-67 | 2.5-<10%  |
|  | Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336                                      |           |
| CAS: 7429-90-5<br>EINECS: 231-072-3<br>Reg.nr.: 01-2119529243-45 | aluminium powder (stabilized)/ manufacturer classification<br>F R11                         | 2.5-<10%  |
|  | Flam. Sol. 1, H228  |           |
| CAS: 64742-48-9<br>EINECS: 265-150-3<br>Reg.nr.:01-2119463258-33 | Naphtha (petroleum), hydrotreated heavy, benzene content < 0,1%<br>Xn R65                   | 0.1-<2.5% |
|  | Asp. Tox.1, H304  |           |
| CAS: 78-83-1<br>EINECS: 201-148-0<br>Reg.nr.:01-2119484609-23    | butanol<br>Xi R37/38-41<br>R10-67   | 1-<2.5%   |
|  | Flam. Liq. 3, H226; Eye Dam. 1, H318; Skin Irrit. 2, H315; STOT SE 3, H335-H336             |           |

Additional information: For the wording of the listed risk phrases refer to section 16.

### **4- FIRST - AID MEASURE**

#### **Description of first aid measures**

After inhalation: Supply fresh air; consult doctor in case of complaints.

After skin contact: Immediately wash with water and soap and rinse thoroughly.

After eye contact: Rinse opened eye for several minutes under running water.

After swallowing: If symptoms persist consult doctor.

**Most important symptoms and effects, both acute and delayed**

No further relevant information available.

**Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

## **5- FIRE - FIGHTING MEASURE**

**Extinguishing media**

**Suitable extinguishing agents:** CO<sub>2</sub>, sand, extinguishing powder. Do not use water.

**For safety reasons unsuitable extinguishing agents:** Water with full jet

**Special hazards arising from the substance or mixture**

No further relevant information available.

**Advice for firefighters**

**Protective equipment:** No special measures required.

## **6- ACCIDENTAL RELEASE MEASURE**

**Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

**Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

**Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

**Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

## **7- HANDLING AND STORAGE**

**Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

**Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.

Chamäleon GmbH- Safety Data Sheet

Protect against electrostatic charges.

**Conditions for safe storage, including any incompatibilities**

**Storage:**

**Requirements to be met by storerooms and receptacles:** No special requirements.

**Information about storage in one common storage facility:** Store away from foodstuffs.

**Further information about storage conditions:** Keep container tightly sealed.

**Storage class:** 3

**Specific end use(s)** No further relevant information available.

## **8 – EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Additional information about design of technical facilities:** No further data; see item 7.

**Control parameters**

|   |   |
|---|---|
| Ingredients with limit values that require monitoring at the workplace: |   |
| 123-86-4 n-butyl acetate  |   |
| WEL   | Short-term value: 966 mg/m <sup>3</sup> , 200 ppm<br>Long-term value: 724 mg/m <sup>3</sup> , 150 ppm |
| 7429-90-5 aluminium powder (stabilized)/ manufacturer classification    |   |
| WEL   | Long-term value: 10* 4** mg/m <sup>3</sup><br>*inhalable dust **respirable dust                       |
| 78-83-1 butanol   |   |
| WEL   | Short-term value: 231 mg/m <sup>3</sup> , 75 ppm<br>Long-term value: 154 mg/m <sup>3</sup> , 50 ppm   |

Additional information: The lists valid during the making were used as basis.

**Exposure controls**

**Personal protective equipment:**

**General protective and hygienic measures:** Wash hands before breaks and at the end of work.

**Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

**Protection of hands:**

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/the chemical mixture.

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

**Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

**Eye protection:** Tightly sealed goggles

## 9 – PHYSICAL AND CHEMICAL PROPERTIES

|  |   |
|--|---|
| <b>Information on basic physical and chemical properties</b> |   |
| <b>General Information</b>                                   |   |
| <b>Appearance:</b>   |   |
| <b>Form:</b>   | <i>Fluid</i>  |
| <b>Colour:</b>   | <i>According to product specification</i>   |
| <b>Odour:</b>  | <i>Characteristic</i>   |
| <b>Odour threshold:</b>                                      | <i>Not determined.</i>  |
| <b>pH-value:</b>   | <i>Not determined.</i>  |
| <b>Change in condition</b>                                   |   |
| <b>Melting point/Melting range:</b>                          | <i>Undetermined.</i>  |
| <b>Boiling point/Boiling range:</b>                          | <i>124°C</i>  |
| <b>Flash point:</b>  | <i>27 °C (DIN 53213)</i>  |
| <b>Flammability (solid, gaseous):</b>                        | <i>Not applicable.</i>  |
| <b>Ignition temperature:</b>                                 | <i>370 °C (DIN 51794)</i>   |
| <b>Decomposition temperature:</b>                            | <i>Not determined.</i>  |
| <b>Self-igniting:</b>  | <i>Product is not selfigniting.</i>   |
| <b>Danger of explosion:</b>                                  | <i>Product is not explosive. However, formation of explosive air/ vapour mixtures are possible.</i> |
| <b>Explosion limits:</b>                                     |   |
| <b>Lower:</b>  | <i>1.2 Vol %</i>  |
| <b>Upper:</b>  | <i>7.5 Vol %</i>  |
| <b>Vapour pressure at 20°C:</b>                              | <i>10.7 hPa</i>   |
| <b>Density at 20°C:</b>                                      | <i>0.941 g/cm<sup>3</sup> (DIN 53217)</i>   |
| <b>Relative density</b>                                      | <i>Not determined.</i>  |
| <b>Vapour density</b>  | <i>Not determined.</i>  |
| <b>Evaporation rate</b>                                      | <i>Not determined.</i>  |
| <b>Solubility in / Miscibility with water:</b>               |   |
| <i>Not miscible or difficult to mix.</i>                     |   |
| <b>Partition coefficient (n-octanol/ water):</b>             |   |
| <i>Not determined.</i>                                       |   |
| <b>Viscosity:</b>  |   |
| <b>Dynamic:</b>  | <i>Not determined.</i>  |
| <b>Kinematic at 20 °C:</b>                                   | <i>75 s (DIN 53211/4)</i>   |

|                                   |  |
|-----------------------------------|--|
| <b>Solvent content:</b>           |  |
| <b>VOC (EC)</b>                   | 66.57 %                                    |
| <b>Solids content (weight-%):</b> | 35.9 %                                     |
| <b>Other information</b>          | No further relevant information available. |

## 10- STABILITY AND REACTIVITY

**Reactivity** No further relevant information available.

**Chemical stability**

**Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

**Possibility of hazardous reactions:** No dangerous reactions known.

**Conditions to avoid:** No further relevant information available.

**Incompatible materials:** No further relevant information available.

**Hazardous decomposition products:** Carbon monoxide.

## 11- TOXICOLOGICAL INFORMATION

**Information on toxicological effects**

**Acute toxicity:**

|   |      |                   |
|---|------|-------------------|
| <b>LD/LC50 values relevant for classification:</b>  |      |                   |
| 64742-95-6 Solvent naphtha (petroleum), light arom. |      |                   |
| Oral  | LD50 | >2000 mg/kg (rat) |
| Dermal  | LD50 | >2000 mg/kg (rab) |

**Primary irritant effect:**

**Skin corrosion/irritation** Based on available data, the classification criteria are not met.

**Serious eye damage/irritation**

Causes serious eye irritation.

**Respiratory or skin sensitisation** Based on available data, the classification criteria are not met.

**CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

**Germ cell mutagenicity** Based on available data, the classification criteria are not met.

**Carcinogenicity** Based on available data, the classification criteria are not met.

**Reproductive toxicity** Based on available data, the classification criteria are not met.

**STOT-single exposure**

May cause drowsiness or dizziness.

**STOT-repeated exposure** Based on available data, the classification criteria are not met.

**Aspiration hazard** Based on available data, the classification criteria are not met.

## **12 – ECOLOGICAL INFORMATION**

### **Toxicity**

**Aquatic toxicity:** No further relevant information available.

**Persistence and degradability** No further relevant information available.

**Bioaccumulative potential** No further relevant information available.

**Mobility in soil** No further relevant information available.

### **Ecotoxicological effects:**

**Remark:** Harmful to fish

### **Additional ecological information:**

#### **General notes:**

Water hazard class 2 (German Regulation): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

#### **Results of PBT and vPvB assessment**

PBT: Not applicable.

vPvB: Not applicable.

**Other adverse effects** No further relevant information available.

## **13– DISPOSAL CONSIDERATION**

### **Waste treatment methods**

#### **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

| European waste catalogue |   |
|--------------------------|---|
| 08 01 11*                | waste paint and varnish containing organic solvents or other dangerous substances |

#### **Uncleaned packaging:**

**Recommendation:** Disposal must be made according to official regulations.

## **14– TRANSPORT INFORMATION**

### **UN-Number**

ADR, IMDG, I AT A

UN 1263

### **UN proper shipping name**

ADR

1263 PAINT, special provision 640E

IMDG, I AT A

PAINT

### **Transport hazard class(es)**

## ADR



Class 3 (F1) Flammable liquids.  
Label 3

## IMDG, I ATA



Class 3 Flammable liquids.  
Label 3

## Packing group

ADR, IMDG, IATA III

## Environmental hazards:

Marine pollutant: No

## Special precautions for user

Warning: Flammable liquids.

Danger code (Kemler): 30

EMS Number: F-E,S-E

## Transport in bulk according to Annex II of

MARPOL and the IBC Code Not applicable.

## Transport/Additional information:

### ADR

Transport category 3  
Tunnel restriction code D/E

### IMDG

Limited quantities (LQ) 5L

## UN "Model Regulation":

UN 1263 PAINT, SPECIAL PROVISION 640E, 3, III, (D/E)

## **15 – REGULATORY INFORMATION**

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

**Directive 2012/18/EU**

**Named dangerous substances - ANNEX I** None of the ingredients is listed.

**National regulations:**

| Class | Share in % |
|-------|------------|
| NK    | 50-100     |

**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## **16-OTHER INFORMATION**

**Relevant phrases**

H226 Flammable liquid and vapour.  
H228 Flammable solid.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

R10 Flammable.  
R11 Highly flammable.  
R37 Irritating to respiratory system.  
R37/38 Irritating to respiratory system and skin.  
R41 Risk of serious damage to eyes.  
R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.  
R65 Harmful: may cause lung damage if swallowed.  
R66 Repeated exposure may cause skin dryness or cracking.  
R67 Vapours may cause drowsiness and dizziness.

The information contained in these sheets is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects and should not be construed as any guarantee of technical performance or suitability for particular applications.